



	AT60-20	4-08141-	08141-16				
	PART NUMBER			DESCRIPTION			
QUANTITY			MAT	ERI	ALS LIST		
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Toterances are as follows: 1 PL DEC 30.10 3) Note reference = MATERIAL SPECIFICATIONS: PROCESS SPECIFICATIONS:		SIGNATURES		DATE	Amphenol		
		DRAWN: IAN		02MAR21			
		CHECKED:	ORION	03MAR21	Sine Systems - www.amphenol-sine.com		
		ENGINEER:			44724 Morley Drive Clinton Township, MI 48036		
		APPROVAL:	TOMMY	04MAR21			
		CUSTOMER:			CONTACT,PIN,SIZE 8, 16MM² WIRE RANGE,NICKEL PLATED		
		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SILBIECT TO NORMAL					
PROCESS SPECIFICATIONS.					B C AT60-204-08141-16	A1	
NEXT ASS'Y:		MANUFACTURING VARIATIONS.		S.	SCALE: NONE SHEET 1 OF	1	

NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL: COPPER ALLOY, NICKEL PLATED

2. CONTACT SIZE: 8#

3. SPECIFICATIONS:

3.1 CURRENT RATING: 60 AMP

3.2 CONTACT MILLIVOLT DROP: 60 MILLIVOLT DROP @ 60 AMP TEST CURRENT. 3.3 ROHS COMPLIANT

4. RECOMMENDED WIRE RANGE: 6AWG(16.0-13.0mm²)

5. AVAILABLE PNEUMATIC CRIMP TOOL: WA23

6. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY