


CAT 5E UTP Outdoor Cable

pro-POWER



RoHS
Compliant

Specifications:

Designed of cable

Inner conductor	: Single Bare Copper (0.49mm ±0.005mm)
Insulation	: HDPE
Insulation Dia	: 0.9mm ±0.05mm
Core colour	: White-Blue; White-Orange; White-Green & White-Brown
Jacket Material	: PVC
Colour	: White
Size	: 5.8mm ±0.2mm
Wall thickness	: 0.8mm
Second Jacket	: PE
Colour	: Black
Size	: 6.4mm ±0.2mm
Wall Thickness	: 0.3mm

Electric data at 20°C

Conductor resistance	: ≤96Ω/kM
Insulation resistance	: ≥5,000M Ω × kM
Testing voltage	: wire/wire 50Hz 1min=1.5kV
Permissible temperature	: -10°C to 60°C

Other Electric data:

Frequency	Impedance	RL	ATT	NEXT	ELFEXT	PSNEXT	PSELFEXT	SKW	NVP
Mhz	ohm	≥dB/100M	≤dB/100M	≥dB/100M	≥dB/100M	≥dB/100M	≥dB/100M	≤ns/100M	
1	100±15	20	2.04	65.3	63.8	62.3	60.8	≤45	66%
4		23	4.1	56.3	51.7	53.3	48.7		
10		25	6.5	50.3	43.8	47.3	40.8		
16		25	8.2	47.3	39.7	44.3	36.7		
20		25	9.3	44.5	37.7	42.8	34.7		
31.25		23.6	11.6	42.9	33.9	39.9	30.9		
62.5		21.5	17	38.4	27.8	35.4	24.8		
100		20.1	22	35.3	23.8	32.3	20.8		

Part Number Table

Description	Part Number
CAT 5E Cable UTP Outdoor, 305m	CAT5EOUTDOOR

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER