E40097

Screw-in adapter for process sensors



Adapter SI0/G1/2/MS

Г

ApplicationApplicationfor industrial applicationsMedialiquids and gasesPressure rating[bar]3030Tests / approvalsPressure Equipment DirectiveA possible classification to PED depends on the application and has to be carried out by the user / operator.Safety instructionsThe compatibility between medium and product material has to be checked in all applications.Mechanical dataVeightWeight[g]Dimensions[mm]Materialsbrass (2.0401)Sensor connectionG 1/2Insertion depth[mm]21; (measuring probe SID, SFD, TN)AccessoriesSealings: 1, AFM	M18 x 1,5 0 5 5 27 G1/2			
Medialiquids and gasesPressure rating[bar]30Tests / approvalsPressure Equipment DirectiveA possible classification to PED depends on the application and has to be carried out by the user / operator.Safety instructionsThe compatibility between medium and product material has to be checked in all applications.Mechanical dataVeightWeight[g]Dimensions[mm]Thread designationM18 x 1.5Materialsbrass (2.0401)Sensor connectionM18 x 1,5 internal threadProcess connectionG 1/2Insertion depth[mm]Accessories	Application			
Pressure rating[bar]30Tests / approvalsA possible classification to PED depends on the application and has to be carried out by the user / operator.Pressure Equipment DirectiveA possible classification to PED depends on the application and has to be carried out by the user / operator.Safety instructionsThe compatibility between medium and product material has to be checked in all applications.Mechanical dataWeight[g]Weight[g]59.2Dimensions[mm]M18 x 1.5Thread designationM18 x 1.5Materialsbrass (2.0401)Sensor connectionM18 x 1,5 internal threadProcess connectionG 1/2Insertion depth[mm]21; (measuring probe SID, SFD, TN)AccessoriesInternal	Application		for industrial applications	
Tests / approvalsPressure Equipment DirectiveA possible classification to PED depends on the application and has to be carried out by the user / operator.Safety instructionsThe compatibility between medium and product material has to be checked in all applications.Mechanical dataWeight [g] Dimensions [mm]M18 x 1.5M18 x 1.5Thread designationM18 x 1.5Materialsbrass (2.0401)Sensor connectionM18 x 1,5 internal threadProcess connectionG 1/2Insertion depth [mm]21; (measuring probe SID, SFD, TN)AccessoriesInsertion depth	Media		liquids and gases	
Pressure Equipment DirectiveA possible classification to PED depends on the application and has to be carried out by the user / operator.Safety instructionsThe compatibility between medium and product material has to be checked in all applications.Mechanical dataVeight [g]Weight [g]59.2Dimensions [mm]M18 x 1.5Thread designationM18 x 1.5Materialsbrass (2.0401)Sensor connectionM18 x 1,5 internal threadProcess connectionG 1/2Insertion depth [mm]21; (measuring probe SID, SFD, TN)AccessoriesImmediate	Pressure rating	[bar]	30	
Pressure Equipment Directiveapplication and has to be carried out by the user / operator.Safety instructionsThe compatibility between medium and product material has to be checked in all applications.Mechanical dataWeight[g]Weight[g]59.2Dimensions[mm]M18 x 1.5Thread designationM18 x 1.5Materialsbrass (2.0401)Sensor connectionM18 x 1,5 internal threadProcess connectionG 1/2Insertion depth[mm]AccessoriesImm]	Tests / approvals			
Safety instructionsmaterial has to be checked in all applications.Mechanical dataWeight[g]Dimensions[mm]Thread designationM18 x 1.5Materialsbrass (2.0401)Sensor connectionM18 x 1,5 internal threadProcess connectionG 1/2Insertion depth[mm]Accessories	Pressure Equipment Directive			
Weight[g]59.2Dimensions[mm]M18 x 1.5Thread designationM18 x 1.5Materialsbrass (2.0401)Sensor connectionM18 x 1,5 internal threadProcess connectionG 1/2Insertion depth[mm]Accessories	Safety instructions			
Dimensions[mm]Dimensions[mm]Thread designationM18 x 1.5Materialsbrass (2.0401)Sensor connectionM18 x 1,5 internal threadProcess connectionG 1/2Insertion depth[mm]Accessories	Mechanical data			
Thread designationM18 x 1.5Materialsbrass (2.0401)Sensor connectionM18 x 1,5 internal threadProcess connectionG 1/2Insertion depth[mm]Accessories	Weight	[g]	59.2	
Materialsbrass (2.0401)Sensor connectionM18 x 1,5 internal threadProcess connectionG 1/2Insertion depth[mm]Accessories	Dimensions	[mm]	M18 × 1.5	
Sensor connection M18 x 1,5 internal thread Process connection G 1/2 Insertion depth [mm] Accessories	Thread designation		M18 x 1.5	
Process connection G 1/2 Insertion depth [mm] Accessories	Materials		brass (2.0401)	
Insertion depth [mm] 21; (measuring probe SID, SFD, TN) Accessories Image: Comparison of the second se	Sensor connection		M18 x 1,5 internal thread	
Accessories	Process connection		G 1/2	
	Insertion depth	[mm]	21; (measuring probe SID, SFD, TN)	
Accessories (supplied) sealings: 1, AFM	Accessories			
	Accessories (supplied)		sealings: 1, AFM	
Remarks	Remarks			
Remarks In applications >30 bar use a suitable high-pressure adapter.	Remarks		In applications >30 bar use a suitable high-pressure adapter.	
Pack quantity 1 pcs.	Pack quantity		1 pcs.	