

Digitrip Power Supply

Powering Business Worldwide

Part no. IZMX-DT-PS-1 Article no. 183969 Catalog No. 70C1305G04

Delivery programme

| Product range | | | Accessories |
|-----------------------|---------|---|--|
| Accessories | | | Options / accessories trip blocks |
| Accessories | | | Power supply |
| | | | Generally speaking, an external power supply is not required for the trip blocks' protective functions. For the trip blocks, it is recommended to use an external power supply in order to adjust additional functions (not basic protection functions) with the cursor and display Alternatively, the user can apply 24 VDC to terminals 19, 20 or establish a connection using the USB port. |
| Rated control voltage | U_{s} | V | 24 V DC |
| For use with | | | IZMX16 IZMX40 |

Design verification as per IEC/EN 61439

| Technical data for design verification | | |
|--|----|-----|
| Operating ambient temperature min. | °C | -25 |
| Operating ambient temperature max. | °C | 70 |

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Low-voltage switch technology (accessories) / Component for low-voltage switch technology (accessories) (ecl@ss8.1-27-37-92-01 [AKN570010])

| Type of accessory | | - |
|-------------------|--|---|