

TECHNICAL DATA SHEET

PRO-ELEC

1.5Kva Transformer Twin 16A Sockets PEL00143

**RoHS
Compliant**

Specification	
Description	Material
Case and lid	Glass Reinforced Plastic (GRP)
Cable	1.5 mm ² 3 core rubber Cable – H07RN-F
Cable length	1500mm
Cable Colour	Black
Plug	230V 13A BS UK 3 pin plug (to BS 1363/A) with 13A fuse (to BS 1362)
Output Socket	2x110V 16Amp 2P+E, IP44 rated to EN 60309
Overload switch	6Amp
Cont. Rating	900VA
Tool Rating	1500VA
IP rating	IP44 to EN 60309
Safety Level	Class I

Input Voltage	Output Voltage	Current	Standard
220-240V AC 50/60Hz	AC 110V C.T.E	1.5KVA	BS1362 BS1363/A)



Conditions of use

1. Ambient temperature in the range -5° C to +40° C, the average value over 24 hours not exceeding 25° C.
2. Situation not subject to exposure to direct radiation from the sun or other source of heat like to raise temperatures above the limits specified in 1.
3. Altitude not exceeding 2000 metres above sea level;
4. Atmosphere not subject to abnormal pollution by smoke, chemical fumes, rain, spray, prolonged periods of high humidity or other abnormal conditions.

Important Notice : This data sheet and its contents (the "Information") belong to pro-ELEC. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but pro-ELEC assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where pro-ELEC was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict pro-ELEC's liability for death or personal injury resulting from its negligence.

PRO-ELEC