



SIMATIC ET 200SP, PROFINET, 2-port interface module IM 155-6PN/2 High Feature, 1 slot for BusAdapter, max. 64 I/O modules and 16 ET 200AL modules, S2 redundancy, multi-hotswap, 0.25 ms, isochronous mode, optional PN strain relief, including server module

General information	
Product type designation	IM 155-6 PN/2 HF
HW functional status	From FS02
Firmware version	V4.2
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Module swapping during operation (hot swapping)</li> </ul>	Yes; Multi-hot swapping
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Tool changer</li> </ul>	Yes; Docking station and docking unit
<ul style="list-style-type: none"> <li>Local coupling, IO data</li> </ul>	No
<ul style="list-style-type: none"> <li>Local coupling, data records</li> </ul>	No
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	STEP 7 V15.1 or higher
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>	Configurable via GSD file
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	GSDML V2.3
Configuration control	
via dataset	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Mains buffering	
<ul style="list-style-type: none"> <li>Mains/voltage failure stored energy time</li> </ul>	10 ms
Input current	
Current consumption, max.	700 mA
Inrush current, max.	4.5 A
$I^2t$	0.25 A <sup>2</sup> ·s
Power loss	
Power loss, typ.	2.4 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Address space per module, max.</li> </ul>	288 byte; For input and output data respectively
Address space per station	
<ul style="list-style-type: none"> <li>Address space per station, max.</li> </ul>	1 440 byte; Dependent on configuration
Hardware configuration	
Rack	

<ul style="list-style-type: none"> <li>Quantity of operable ET 200SP modules, max.</li> <li>Quantity of operable ET 200AL modules, max.</li> </ul>	64 16
<b>Submodules</b>	
<ul style="list-style-type: none"> <li>Number of submodules per station, max.</li> </ul>	256
<b>Time stamping</b>	
Accuracy	10 ms
<b>Interfaces</b>	
Number of PROFINET interfaces	1; 2 ports (switch)
<b>1. Interface</b>	
<b>Interface types</b>	
<ul style="list-style-type: none"> <li>Number of ports</li> <li>integrated switch</li> <li>BusAdapter (PROFINET)</li> </ul>	2; via BusAdapter Yes Yes; compatible BusAdapters: BA 2x RJ45, BA 2x M12, BA 2x FC, BA 2x LC, BA LC/RJ45, BA LC/FC, BA 2x SCRJ, BA SCRJ/RJ45, BA SCRJ/FC,
<b>Protocols</b>	
<ul style="list-style-type: none"> <li>PROFINET IO Device</li> <li>Open IE communication</li> <li>Media redundancy</li> </ul>	Yes Yes Yes; PROFINET MRP
<b>Interface types</b>	
<b>RJ 45 (Ethernet)</b>	
<ul style="list-style-type: none"> <li>Transmission procedure</li> <li>10 Mbps</li> <li>100 Mbps</li> <li>Autonegotiation</li> <li>Autocrossing</li> </ul>	PROFINET with 100 Mbit/s full duplex (100BASE-TX) No Yes; PROFINET with 100 Mbit/s full duplex (100BASE-TX) Yes Yes
<b>Protocols</b>	
<b>Number of connections</b>	
<ul style="list-style-type: none"> <li>Number of MtM communication relationships/connections, max.</li> </ul>	16
<b>PROFINET IO Device</b>	
<b>Services</b>	
— IRT	Yes; 250 $\mu$ s, 500 $\mu$ s, 1 ms, 2 ms, 4 ms additionally with IRT with high performance: 250 $\mu$ s to 4 ms in 125 $\mu$ s frame
— PROFIenergy	Yes
— Prioritized startup	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	4
<b>Redundancy mode</b>	
<ul style="list-style-type: none"> <li>PROFINET system redundancy (S2)</li> <li>H-Sync forwarding</li> </ul>	Yes; NAP S2 Yes
<b>Media redundancy</b>	
— MRP	Yes
— MRPD	No
<b>Open IE communication</b>	
<ul style="list-style-type: none"> <li>TCP/IP</li> <li>SNMP</li> <li>LLDP</li> </ul>	Yes Yes Yes
<b>Isochronous mode</b>	
Equidistance	Yes
shortest clock pulse	250 $\mu$ s
max. cycle	4 ms
Bus cycle time (TDP), min.	250 $\mu$ s
Jitter, max.	1 $\mu$ s
<b>Interrupts/diagnostics/status information</b>	
Status indicator	Yes
Alarms	Yes
Diagnostics function	Yes
Diagnostics indication LED	

<ul style="list-style-type: none"> <li>• RUN LED</li> <li>• ERROR LED</li> <li>• MAINT LED</li> <li>• Monitoring of the supply voltage (PWR-LED)</li> <li>• Connection display LINK TX/RX</li> </ul>	Yes; green LED Yes; red LED Yes; Yellow LED Yes; green PWR LED Yes; 2x green link LEDs on BusAdapter
<b>Potential separation</b>	
between backplane bus and electronics	No
between PROFINET and all other circuits	Yes
between supply and all other circuits	No
<b>Isolation</b>	
Isolation tested with	707 V DC (type test)
<b>Standards, approvals, certificates</b>	
Network loading class	3
Security level	According to Security Level 1 Test Cases V1.1.1
<b>Ambient conditions</b>	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>• horizontal installation, min.</li> <li>• horizontal installation, max.</li> <li>• vertical installation, min.</li> <li>• vertical installation, max.</li> </ul>	-30 °C; No condensation 60 °C -30 °C; No condensation 50 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> <li>• Installation altitude above sea level, max.</li> </ul>	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
<b>connection method / header</b>	
ET-Connection	
<ul style="list-style-type: none"> <li>• via BU/BA Send</li> </ul>	Yes; + 16 ET 200AL modules
<b>Mechanics/material</b>	
Strain relief	Yes; Optional
<b>Dimensions</b>	
Width	50 mm
Height	117 mm
Depth	74 mm
<b>Weights</b>	
Weight, approx.	120 g; without BusAdapter
<b>last modified:</b>	3/2/2021 