

300Mbps Wireless N Router

N300 with Proven Stability









Highlights

Reliable Network Connection

Equipped with two 5dBi antennas, the TL-WR841N can enhance wireless signal transmission and reception. With the 4 fast Ethernet ports, it provides reliable Wi-Fi and wired connection for medium-sized homes, letting your family enjoy fast Wi-Fi together on every smartphone, tablet and laptop.







Wireless N Speed & Range

Complying with the IEEE 802.11n standard, TL-WR841N can establish a wireless network and get up to 15X the speed and 5X the range of conventional 11g products. Also, with transmission rates up to 300Mbps.



Features







Reliability

- · Wireless N Speed 300Mbps Wi-Fi speed meets your daily internet needs
- · 802.11 n Backward compatible with 802.11b/g products
- \cdot MIMO Technology 2 x 2 MIMO technology increases efficiency for streaming & gaming
- Easy Bandwidth Management Bandwidth Control allocates necessary speed of each connected device to ensure quality of multimedia streaming

Ease of Use

- Intuitive Web UI– Ensures quick and simple installation without hassle
- \cdot Fast Encryption One-touch WPA wireless security encryption with the WPS button
- · Easy On/Off Turn On/Off wireless radio using the Wi-Fi On/Off button
- · Power On/Off Conveniently power on or off your router as required
- Hassle-free Management with Tether App Network management is made easy with the TP-Link Tether App, available on any Android or iOS device

Security

- Guest Network Keep your main network secure by creating a separate network for friends and visitors
- · Access Control Establish a whitelist or blacklist to allow or block certain devices from accessing the internet
- Parental Controls Manage when and how connected devices
 can access the internet
- $\cdot \ \, \text{Encryptions for Secure Network-WPA-PSK/WPA2-PSK} \\ \, \text{encryptions provide active protection against security threats} \\$

TP-Link 300Mbps Wireless N Router TL-WR841N

Specifications

Hardware

- · Ethernet Ports: 4 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port
- · Buttons: WPS/Reset Button, Power On/Off Button, Wi-Fi On/Off Button
- · Antennas: 2 5dBi fixed Omni Directional Antennas (RP-SMA)
- · External Power Supply: 9VDC / 0.6A
- Dimensions (W x D x H): 7.6 x 5.3 x 1.3 in. (192 x 134 x 33 mm)



Wireless

- · Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE
- · Frequency: 2.4-2.4835GHz
- · Signal Rate:

11n: Up to 300Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)

· Reception Sensitivity:

270M: -70dBm@10% PER

130M: -74dBm@10% PER

108M: -74dBm@10% PER

54M: -77dBm@10% PER 11M: -87dBm@8% PER

6M: -90dBm@10% PER

1M: -98dBm@8% PER

- Wireless Function: Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
- · Wireless Security: WEP, WPA/WPA2, WPA-PSK/WPA-PSK2

Specifications

Software

- WAN Type: Dynamic IP, Static IP, PPPoE, PPTP(Dual Access), L2TP(Dual
- · DHCP: Server, DHCP Client List, Address Reservation
- · Quality of Service: WMM, Bandwidth Control
- · Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
- · Dynamic DNS: DynDns, Comexe, NO-IP
- · Access Control: Parental Control, Local Management Control, Host list, Access Schedule, Rule Management
- · Firewall Security: DoS, SPI Firewall, IP and MAC Address Binding
- · Protocols: IPv4, IPv6
- · Management: Access Control, Local Management, Remote Management
- · Guest Network: 2.4GHz guest network

Others

- · Certification
- CF. FCC. RoHS. Wi-Fi
- System Requirements

Microsoft Windows 10/8.1/8/7/Vista/XP/2000/NT/98SE, MAC OS, NetWare, UNIX or Linux

Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser

Cable or DSI Modem

Subscription with an Internet Service Provider (for internet access)

· Environment

Operating Temperature: 0°C~40°C (32°F ~104°F)

Storage Temperature: -40°C~70°C (-40°F ~158°F)

Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

Package Contents

300Mbps Wireless N Router TL-WR841N

Power Adapter

R.J-45 Ethernet Cable

Quick Installation Guide



For more information, please visit

http://www.tp-licin.com or scan the QR code left http://www.tp-link.com/en/products/details/cat-9_TL-WR841N.html

is are subject to change without notice. TP-Link is a registered trademark of TP-Link Technologies CO., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. No part of the specifications may be reproduced in any form or by any means or used derivative such as translation, transformation, or adaptation without permission from TP-Link Technologies CO., Ltd.

Teless speed of typic 3.00Mpc; is the theoretic of a data rate derived from EEE standard 802.11 specifications. Actual data throughput and wireless coverage will vary due to network conditions and environmental factors including volume of network track, building materials and construction, network track and data trace derived from EEE standard 802.11 specifications. Actual data throughput and wireless coverage.

www.tp-link.com

TP-Link 300Mbps Wireless N Router TL-WR841N