

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [1200878711](#)  
**Status:** **Active**  
**Overview:** Brad M8 and M12 Cordsets with Knurled Hexnuts and WSOR Cable  
**Description:** Nano-Change (M8) Double-Ended Cordset with Knurled Hexnut, 4 Poles, Male (Straight) to Female (Straight), 24 AWG, Black TPU WSOR Cable, 2.0m (6.56') Length

**Documents:**

[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**General**

|                    |  |
|--------------------|--|
| Product Family     | Industrial Cordsets  |
| Series             | <a href="#">120087</a>   |
| Connector End A    | Nano-Change (M8)   |
| Connector End B    | Nano-Change (M8)   |
| IP Rating          | IP67   |
| Material - Contact | Brass  |
| Overview           | <a href="#">Brad M8 and M12 Cordsets with Knurled Hexnuts and WSOR Cable</a> |
| Product Name       | Nano-Change (M8)   |
| Region             | Europe   |
| Taxonomy           | Circular Industrial Cordsets   |
| Type               | Double Ended   |
| UPC                | 889056073974   |

**Physical**

|                               |                          |
|-------------------------------|--------------------------|
| Cable Diameter                | 4.80mm (.189")           |
| Cable Length                  | 2.0m (6.56')             |
| Color - Cable Jacket          | Black                    |
| Coupling Style                | Knurled Hexnut, Threaded |
| Gender                        | Female-Male              |
| Keyway                        | A-coded                  |
| LED Indicator                 | No                       |
| Material - Cable Jacket       | TPU                      |
| Material - Connector Body     | TPU                      |
| Material - Coupling Nut       | Nickel-plated Brass      |
| Material - O-Ring             | Fluoro-elastomer         |
| Material - Plating Mating     | Gold                     |
| Net Weight                    | 78.653/g                 |
| Orientation                   | Straight to Straight     |
| Poles                         | 4                        |
| Temperature Range - Operating | -25° to +85°C            |
| Wire Size AWG                 | 24                       |
| Wire/Cable Type               | UL 21215                 |

**Electrical**

|                               |                 |
|-------------------------------|-----------------|
| Current - Maximum per Contact | 3.0A            |
| Voltage - Maximum             | 60V AC / 75V DC |

**Material Info**

|                    |               |
|--------------------|---------------|
| Engineering Number | 444030B41M020 |
|--------------------|---------------|

**Reference - Drawing Numbers**

|               |                |
|---------------|----------------|
| Sales Drawing | 1200878716-000 |
|---------------|----------------|



**EU ELV**

**Not Reviewed**

**EU RoHS**

**Not Reviewed**

**REACH SVHC**

Not Reviewed

**Halogen-Free**

**Status**

**Not Reviewed**

For more information, please visit [Contact US](#)

China ROHS

Not Reviewed

ELV

Not Reviewed

RoHS Phthalates

Not Reviewed

**Search Parts in this Series**

[120087 Series](#)