Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources							
Supplier's name or trade mark: Hera GmbH & Co KG							
Supplier's address: FE, Dieselstraße 9, 32130 Enger Herford, DE							
Model identifier: Dynamic FAQ 68-LED							
Type of light source:							
Lighting technology used:	LED	Non-directional or directional:	DLS				
Light source cap-type	nein						
(or other electric interface)							
Mains or non-mains:	NMLS	Connected light source (CLS):	Nein				
Colour-tuneable light source:	Nein	Envelope:	-				
High luminance light source:	Nein						
Anti-glare shield:	Nein	Dimmable:	Only with specific dimmers				
Product parameters							
Parameter	Value	Parameter	Value				
General product parameters:							
Energy consumption in on mode (kWh/1000 h), rounded up to the nearest integer		Energy efficiency class	G				
Useful luminous flux (фuse) indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000 or 4 000				
On-mode power (P _{on}) expressed in W	3,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00				
Networked standby power (P _{net} for CLS, expressed in W and rounded to the second decimal	I	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	93				
Outer Height Width	75 75	Spectral power distribution in the	See image in last page				

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	14	range 250 nm to 800 nm, at full-load			
Claim of equival	ent power ^(a)	-	If yes, equivalent power (W)	-		
			Chromaticity coordinates (x and y)	0,431 0,398		
Parameters for directional light sources:						
Peak luminous in	ntensity (cd)	1	Beam angle in degrees, or the range of beam angles that can be set	115		
Parameters for LED and OLED light sources:						
R9 colour rende	ring index value	0	Survival factor	0,00		
the lumen maint	tenance factor	0,00				

(a)'-': not applicable;

