

durabit™

swissbit®

Product Fact Sheet

**Secure microSDHC
Memory Card
for Cameras**

**PS-45u iShield Camera
Series**
UHS-I, MLC

Industrial Temperature Grade

Date: Feb 26, 2021
Revision: 1.00



Product Fact Sheet

PS-45u iShield Camera Series



Product Summary

- **Capacities:** 16 GBytes, 32 GBytes
- **Form Factor:** Standard microSD Memory card form factor – 15.0mm x 11.0mm x 0.7mm (1.0mm)
- **Compliance:** Fully compliant with SD Memory Card specification 2.0 and 3.0 and microSD Memory Card Addendum 4.00
- **Performance:**
 - SD Default speed, SD High speed, SD UHS-I, Speed Class 10
 - Read Performance: Sequential Read up to 16 MBytes/s, Random Read IOPS up to 800
 - Write Performance: Sequential Write up to 13 MBytes/s, Random Write IOPS up to 550
- **Operating Temperature Range¹:**
 - Industrial: -40 °C to 85 °C
- **Operating Voltage:** 2.7...3.6V normal operating voltage (Low-power CMOS technology)
- **Data Retention:** 10 Years @ Life Begin / 1 Year @ Life End
- **Endurance @ Max Capacity²:** 85 TBW (TeraBytes Written)

Product Features

- **Host-agnostic plug-and-play** solution for protecting data recorded on **common cameras**
- **Intended usage:** drone camera, body camera, professional photography (DSLR), dash cam, surveillance camera, action camera, camera traps, and more.
- **Hardware encryption** (AES 256bit) and **access protection** integrated on the memory card
- Supports **loop recording** (e.g. in dashcams) without host modification
- Comes with **user-friendly management** tool (Win, Lin, Mac)

Ordering Information

Product Type	Product Series	Capacity	Part Number
microSD	PS-45u iShield Camera	16 GBytes	SFSD016GN3PM1T0-I-LF-010-SW3
microSD	PS-45u iShield Camera	32 GBytes	SFSD032GN3PM1T0-I-HG-010-SW3

Why Swissbit?

Swissbit strives to create innovative technologies for future market opportunities utilizing a highly skilled in-house research and development team. Swissbit maintains a marketing edge by continuing to manufacture world-class high quality memory and security products and providing customers with both high value and low cost of ownership achieved through efficient processes and procedures.

¹ Adequate airflow is required to ensure the temperature, does not exceed 85°C (industrial temperature card)

² According to JEDEC (JESD471), the time to write the full TBW is a minimum of 18 months. Higher average daily data volume reduces the specified TBW. The values listed are estimates and are subject to change without notice.