- Fastenings at angles up to 30° per side
- Quick feeding of the key into the screw thanks to feeding from various angles
- The key does not slip out of the screw, which reduces the risk of accidents
- No deformation of the screw head thanks to precision fitting of the ball end
- Fastenings at angles up to 25° per side
- Higher torque transmission due to maximum core diameter
- Elongated profile positioning for further use of the L-key
- Thanks to the combination of MagicRing® with the Wiha ball end, inserting and removing screws is possible, even in hard-to-reach locations
- Securely holds screws made of steel and non-magnetic materials such as stainless steel, titanium, aluminium and plastics in any position
- Can be used for all standard screws
- Use for applications in which magnetised fastening tools cannot and may not be used (magnetic environment)!
- Fastenings at angles up to 25° per side
- Securely holds screws made of steel and non-magnetic materials such as stainless steel, titanium, aluminium and plastics in any position
- TORX® and TORX PLUS® screws manufactured according to Camcar Textron specifications
- Use for applications in which magnetised fastening tools cannot and may not be used (magnetic environment)!
- Reduction of the short L-key arm, especially for hard-to-reach screws
- Increase in the hand working space of over 30% and thus a reduction of the risk of injury to the knuckles and fingertips thanks to a 95° bend of the L-key
- Improved access through a reduction of the L-key head height of up to 15%
- \bullet Ball end geometry enables fastening at an angle of up to 25°
- Handles and holders in the same colour depending on the output size
- This provides an overview of the tool assortment



Wiha hexagon L-key (metric).

For Allen screws (metric).



369B Ball end hex L-key, long.

Blade: Chrome-vanadium steel, through-hardened, black finish.

Standards: Based on ISO 2936L.

Application: Especially for screws that are difficult to access.

Extra: The ball end enables the user to work at angles up to 25°.

Order-No.	•	\Box	1	
01391	1.3	74	14	10
05638	1.5	91	15	10
03868	2	101	18	10
03869	2.5	113	20	10
03870	3	128	23	10
03871	4	142	29	10
03872	5	163	33	10
03873	6	184	38	10
03874	8	206	44	10
03875	10	231	50	5
03876	12	259	57	5

For Allen screws (metric). With a screws (metric). 369 SVH1B Display ball end hex L-key sets. Black finish, in ProStar, 9 pcs. Carton display with 10 pieces. Order-No. Content



369 S9B Ball end hex L-key set in ProStar.

Black finish, 9 pcs.

Blade: Chrome-vanadium steel, through-hardened, black finish.

Standards: Based on ISO 2936L.

Application: Especially for screws that are difficult to access.

Extra: Space saving ProStar allows the easy removal of each key without

moving any others.

The ball end enables the user to work at angles up to 25°.

Order-No.	Series						
07186	369 S9B						5
•	369B	1.5	2	2.5	3	4	
		5	6	8	10		



1.5 - 10

369 H9B Hexagon ball end L-key set in Classic holder.

Black finish, 9 pcs.

10 x 369 S9B

07195

Blade: Chrome-vanadium steel, through-hardened, black finish.

Standards: Based on ISO 2936L.

Application: Especially for screws that are difficult to access. Extra: Popular key sizes kept in a well-organised holder.

Simple, rapid operation with solid stopping point for L-keys. The ball end enables the user to work at angles up to 25° .

Order-No.	Series						
03879	369 H9B						5
•	369B	1.5	2	2.5	3	4	
		5	6	8	10		

SB 369 S9B Ball end hex L-key set in ProStar.

Black finish, 9 pcs. Blister packed.

Order-No.	Series							
07193	SB 369 S	SB 369 S9B						
•	369B	1.5	2	2.5	3	4		
		5	6	8	10			

SB 369 H9B Hexagon ball end L-key set in Classic holder. Black finish, 9 pcs.

Blister packed.

Order-No.	Series								
03992	SB 369 H9	SB 369 H9B 10							
•	369B	1.5	2	2.5	3	4			
		5	6	8	10				