

product type designation



RF310R reader

SIMATIC RF300; Reader RF310R (GEN2); RS422 interface (3964R); IP67, -25 to +70 °C, 55x 75x 30 mm, with integrated antenna .

suitability for operation

RF300, ISO 15693 and MOBY E transponder, for connecting to communication modules

radio frequencies

operating frequency / rated value	13.56 MHz
range / maximum	60 mm; Range is dependent on transponder type: observe http://support.automation.siemens.com/WW/view/en/67384964
protocol / with radio transmission	RF300 specific, ISO 15693, ISO 18000-3, ISO 14443
transfer rate / with radio transmission / maximum	106 kbit/s
product feature / multitag-capable	No

electrical data

transfer rate / at the point-to-point connection / serial / maximum	115.2 kbit/s
transmission time / for user data	
• for write access / per byte / typical	0.13 ms
• for read access / per byte / typical	0.13 ms

interfaces

standard for interfaces / for communication	RS422
type of electrical connection	M12, 8-pin

mechanical data

material	PA 12
color	Ti gray
tightening torque / of the screw for securing the equipment / maximum	1.5 N·m
mounting distance / relating to metal surfaces / recommended / minimum	0 mm

supply voltage, current consumption, power loss

supply voltage	
• at DC / rated value	24 V
• at DC	20.4 ... 28.8 V
consumed current / at DC	
• at 24 V / typical	0.06 A

ambient conditions

ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
protection class IP	IP67
shock resistance	EN 60721-3-7 Class 7 M2
shock acceleration	500 m/s ²

vibrational acceleration	200 m/s ²
design, dimensions and weights	
width	55 mm
height	30 mm
depth	75 mm
net weight	0.2 kg
fastening method	4 x M5 screws
wire length	
• for RS 422 interface / maximum	1000 m
product features, product functions, product components / general	
display version	5-color LED
product feature / silicon-free	Yes
standards, specifications, approvals	
certificate of suitability	Radio acc. to R&TTE guidelines EN 300 330, EN 301489, CE, FCC, cULus
certificate of suitability	
• IECEx	No
MTBF	273 y
further information / internet-Links	
Internet-Link	
• to web page: selection aid TIA Selection Tool	https://support.industry.siemens.com/cs/ww/en/view/67384964
• to website: Industrial communication	http://www.siemens.com/ident/rfid
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified:

12/18/2020 