



 <p>Type 722</p>  <p>Suitable desoldering tips, type 722, see page 44</p>  <p>OIRHP200</p>	<p>0DIG20AXT</p> <p>0DIG203A</p> <p>0CU100A</p> <p>0CU103A</p> <p>3N401</p> <p>0720EDJ</p> <p>072100J011</p> <p>072100J012</p> <p>E072400</p> <p>E072600</p> <p>072604/10</p> <p>072605/10</p> <p>3T7260-02</p> <p>3T7260-03</p> <p>0A44</p> <p>0IRHP200</p> <p>0IR5500-01</p> <p>0PH100</p>	<p>DIGITAL 2000 A electronically temp.-controlled desoldering station, 80 W, antistatic, complete with X-TOOL desoldering iron and vaccum station</p> <p><i>consisting of:</i> Electronic station, 230/24 V, 80 W, antistatic*</p> <p>0CU103A* vacuum unit with X-TOOL desoldering iron and holder 0A44</p> <p><i>Accessories / spare parts:</i> Vacuum station* for X-TOOL desoldering iron</p> <p>Prefilter for 0CU103A</p> <p>X-TOOL desoldering iron, 24 V, 2 x 60 W, with desoldering tip 0722ED1226</p> <p>Heating element with temperature sensor for X-TOOL desoldering iron, 24 V, 60 W</p> <p>Heating element for X-TOOL desoldering iron, 24 V, 60 W</p> <p>Desoldering head, complete</p> <p>Solder container, complete</p> <p>Solder filter, cellulose</p> <p>Solder filter cap</p> <p>Front sealing plug</p> <p>Rear sealing plug</p> <p>Holder for X-TOOL desoldering iron, antistatic</p> <p>Electronically temperature-controlled infrared rework heating plate with integrated temperature sensor, 230 V, 800 W, incl. temperature regulator 0RA4500D, 230 V, max. 3,000 W resistive load (see page 23)</p> <p>X-Y PCB table (figure see page 23)</p> <p>PCB holder (figure see page 23)</p>
 <p>Delivery without soldering stations</p>	<p>0STR100</p>	<p>STR 100 stacking rack for 2 soldering stations</p> <p><i>(not suitable for i-CON soldering stations)</i></p>
 <p>Delivery without soldering stations</p>	<p>0STR200</p>	<p>STR 200 stacking rack for 2 soldering stations</p> <p><i>for i-CON soldering stations</i></p>