


Product type designation

Product description

PROFIBUS FC Food Cable

Bus cable (2-core), sold by the meter, unassembled
SIMATIC NET, PROFIBUS FC FOOD BUS CABLE WITH PE-SHEATH FOR APPLICATION IN FOOD AND BEVERAGE INDUSTRY, 2-WIRE, SHIELDED, SOLD BY THE METER, MAX. CONSIGNMENT: 1000M, MIN. ORDERING QUANTITY: 20 M



Suitability for use	For use in the food, beverages and tobacco industries
Cable designation	02YSY (ST) C2Y 1x2x0,64/2,55-150 KF 40
Electrical data	
Damping ratio per length	
<ul style="list-style-type: none"> • at 9.6 kHz / maximum • at 38.4 kHz / maximum • at 4 MHz / maximum • at 16 MHz / maximum 	<p>0.0025 dB/m</p> <p>0.004 dB/m</p> <p>0.022 dB/m</p> <p>0.042 dB/m</p>
Impedance	
<ul style="list-style-type: none"> • Rated value • at 9.6 kHz • at 38.4 kHz • at 3 MHz ... 20 MHz 	<p>150 Ω</p> <p>270 Ω</p> <p>185 Ω</p> <p>150 Ω</p>
Relative symmetrical tolerance	
<ul style="list-style-type: none"> • of the characteristic impedance at 9.6 kHz • of the characteristic impedance at 38.4 kHz • of the characteristic impedance at 3 MHz ... 20 MHz 	<p>10 %</p> <p>10 %</p> <p>10 %</p>
Loop resistance per length / maximum	110 mΩ/m
Shield resistance per length / maximum	9.5 Ω/km
Capacity per length / at 1 kHz	28.5 pF/m
Operating voltage	
<ul style="list-style-type: none"> • RMS value 	100 V

Mechanical data	
Number of electrical cores	2
Design of the shield	Overlapped aluminum-clad foil, sheathed in a braided screen of tin-plated copper wires
Type of electrical connection / FastConnect	Yes
Outer diameter <ul style="list-style-type: none"> • of inner conductor • of the wire insulation • of the inner sheath of the cable • of cable sheath 	0.65 mm 2.55 mm 5.4 mm 8 mm
Symmetrical tolerance of the outer diameter / of cable sheath	0.4 mm
Material <ul style="list-style-type: none"> • of the wire insulation • of the inner sheath of the cable • of cable sheath 	PE PVC PE; Outer cover made of PE is especially suitable for the food processing industry
Color <ul style="list-style-type: none"> • of the insulation of data wires • of cable sheath 	red / green Black
Bending radius <ul style="list-style-type: none"> • with single bend / minimum permissible • with multiple bends / minimum permissible 	30 mm 60 mm
Tensile load / maximum	100 N
Weight per length	67 kg/km

Permitted ambient conditions	
Ambient temperature <ul style="list-style-type: none"> • during operation • during storage • during transport • during installation • Note 	-40 ... +60 °C -40 ... +60 °C -40 ... +60 °C -40 ... +60 °C electrical properties measured at 20 Cel, tests according to DIN 47250 part 4 respectively DIN VDE 0472
Burning behavior	flammable
Chemical resistance <ul style="list-style-type: none"> • to mineral oil • to grease • to water 	oil resistant according to IEC 60811-2-1 (4 h / 70°C) Conditional resistance Conditional resistance
Radiological resistance / to UV radiation	resistant

Product properties, functions, components / general	
Product property <ul style="list-style-type: none"> • halogen-free 	No

- silicon-free

Yes

Standards, specifications, approvals

Certificate of suitability	
• CE marking	Yes
• RoHS conformity	Yes
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	No
• Bureau Veritas (BV)	No
• Det Norske Veritas (DNV)	No
• Germanische Lloyd (GL)	No
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (NK)	No
• Polski Rejestr Statkow (PRS)	No

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/automation/net/catalog
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified:

12.03.2015