Articulated side guides

Technopolymer, stainless steel









































SELF-SUPPORTING STRUCTURE

Acetal resin based (POM) technopolymer, black colour.

PINS

AISI 304 stainless steel.

Polyethylene based (PE) technopolymer, grey colour.

STANDARD EXECUTIONS

- GLB-1-RS: with shaped rollers, spherical contact.
- GLB-1-RC: with cylindrical rollers.
- GLB-1-RT: with shaped rollers, cylindrical contact.

FEATURES AND APPLICATIONS

GLB-1 side guides are modular self-supporting structures for the side guide of products with limited vertical dimensions on conveyor belts (Fig.1).

Particularly suitable for use in wet environments.

Depending on the product to transport, it is recommended to use:

- GLB-1-RS: for the guide of products in cans or in plastic containers;
- GLB-1-RC: for the guide of cardboard products, for a greater fluency;
- GLB-1-RT: for the guide of glass products, in case of accidental

breakage they facilitate the expulsion of debris. The joint in the roller side guides allows an external curvature radius 500 mm, internal curvature radius 350 mm.

Supplied already assembled in modules of 375 mm length, for profiles 40x8 mm.

SPECIAL EXECUTIONS ON REQUEST


- Side guides with self-supporting structure and rollers in different colours.
- Side guides with pins in acetal resin based (POM) technopolymer.


ACCESSORIES ON REQUEST

- PRA-GLB: AISI 304 stainless steel profile for side guides.
- PRB-GLB: AISI 304 stainless steel profile for side guides.



























INOX STAINLESS STEEL

 $\Delta \Delta$

340











ജ

2.2

GLB-1-RS


Code

419161


GLB-1-RC		NOX STAINLESS STEEL
Code	Description	44
419162	GLB-1-RC-46-375	340

Description

GLB-1-RS-46-375



375



Code Description	GLB-1-RT		NOX STAINLESS STEEL
	Code	Description	Δ'Δ
419163 GLB-1-RT-46-375 340	419163	GLB-1-RT-46-375	340

GLB-1-RS

GLB-1-RC

1275