Index Plungers • with rapid locking head 22122.0305



Product Description

Index plungers are used for indexing bores.

Material

Body

Stainless steel 1.4305

Press button

• Thermoplastic POM, red

Locking pin

Stainless steel 1.4305, nickel-plated

Knob

• Thermoplastic PA 6, black-grey, matt

Assembly

The screw length can be adapted by distance collars for index plungers (EH 22120.).

Operation

The locking pin is drawn in and locked by pulling the knob. The projecting red press button indicates the locking position (locking pin drawn in). Pushing the red press button causes the locking pin to jump back into the locking position.

More information


Notes


Knob not removable. Lock nuts have to be purchased separately.

Further products

- Locating Bushings, for index bolts and index plungers
- Distance Collars, for index plungers
 Mounting Blocks, for index bolts and index plungers

Drawing





lock nut 22120.0116 - .0118 (Steel) 22120.0516 - .0518 (Stainless steel)

Order information

Dimensions							ws	Spring load ¹⁾		ß	B		Art. No.
d ₁	d ₂	I ₂	d ₃	I ₁	I ₃	I4		F ₁	F ₂	min.	max.		
-0.02		min.		~				~	~				
-0.04													
[mm]							[mm]	[N]		[°C]	[g]	
stainless steel													
6	M12 x 1,5	6	30	53.5	22	6	19	6.5	19	-30	80	48	22122.0305

1) statistical average value

Accessories

stainless steel	Dimensions d ₂ [mm]	Wrench size [mm]	a	Art. No.
	M12 x 1,5	18	7.6	22120.0516

Compliance

RoHS compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863

Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 10.06.2022

Does not contain Proposition 65 substances

No Proposition 65 substances included https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.