Cable Shielded







RoHS Compliant

PP000712 & PP000713

PP000714

Technical Specifications:

Description	PP000712	PP000713	PP000714
Multi-construction	1 Pair 23 AWG #4144 PVC	2 pair	2 pair

Cable Construction:

Conductor		Bare Copper		
Construction	0.08 × 60	0.08 × 40		
Standard Dia.(mm)	0.71	0.5	58	
Insulation		PE		
Thickness	0.52	0.3	36	
Insulation Dia.(mm)	1.75 ±0.05 × 2C	1.30 ±0.0	05 × 4C	
Insulation Colour		According to customer		
Paper Tape		≥115%		
Braiding		Tinned Copper		
Construction	T0.12 × 144 (95%)	T0.12 × 144 (95%)		
Jacket		PVC		
Thickness(mm)	1.2	0.85		
Dia.(±0.2mm)	6.35	6.2		
Jacket Color	Black	Blue	Black	
Packaging		100M/Wooden Drum		

Electrical Characteristics:

Max. Conductor DC Resistance at 20°C (Ω/Km)	<61.8	</th <th>92</th>	92
Min. Insulation DC Resistance at 20°C (MΩ×Km)	>200		
Rated Temperature(°C)	-20 to +80		
Rated Voltage (V)	600V Rms		
Capacitance core to core (Pf/m)	58.6 Nom	59 Nom	
Capacitance to Ground (Pf/m)	104.8 Nom		
Characteristic Impedance	86Ω	-	-
Inductance	0.72µH/m	0.68	μH/m

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro




Cable Shielded




Design:


PP000712



PP000713



PP000714



Part Number Table

Description	Part Number
Cable, Shielded, 1Pair, 100m, Black	PP000712
Cable, Shielded, 2Pair, 100m, Blue	PP000713
Cable, Shielded, 2Pair, 100m, Black	PP000714

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

