NC machine reamer HSSE with straight shank For universal use up to 1000 $\mbox{N/mm}^{2}$



Application

for cutting H7 fit tolerances in through holes and blind holes on NC machines or conventional machines up to 1000 $\rm N/mm^2.$

 \blacksquare 7-8° left-hand spiral, type D, with centring hole and offset shank

■ good bore hole quality (dimensional tolerance, roundness, surface quality)

Application		Steel (N/mm²)			Stainless steel		Alu		Brass					Graphite					Hard mat.	
		<700	<1000	<1300	marten.	austen.	short	long	short	long	short	long	tics	G(C)FK	GjMW	alloy	alloy	alloy	<55 HRC	<65 HRC
		12	9	7	8	7	17	17	17	17	13	13	13		11	5	5	5		

Art. No.	11628 076					
Cutting material	HSSE					
Tolerance of fit	H7					
Groove type	Left-hand twist, 7-8°					
Tool holding device	HA parallel shank					
Cutting edge diameter	7.6 mm					
Length	117 mm					
Cutting edge length	33 mm					
Projecting length	81 mm					
Shaft diameter	8 mm					
Number of cutting edges	6 PCS					
Surface	Uncoated					
f steel 1000	0.1 mm/U					
DIN	212					

EAN-Code

4050293009507

