

7461 Krafftform pre-set adjustable torque screwdrivers with Rapidaptor quick-release chuck, 1/4 inch, 1,2 Nm
Series 7400 Krafftform Torque Screwdrivers



EAN:	4013288102928	Size:	155x37x37 mm
Part number:	05074716001	Weight:	180 g
Article number:	7400 vor	Country of origin:	CZ
		Customs tariff number:	82054000



- Adjustable Krafftform torque screwdriver with Rapidaptor quick-release chuck
- Suitable for bits with 1/4" hex head drive
- Rapidaptor technology for rapid bit change
- Distinct signal when pre-set value is reached
- Multi-component Krafftform handle for high working speeds

Wera torque screwdriver. Pre-set torque value for all applications where the same, constant torque and repeat accuracy are required. The torque value can be modified within a specific measurement range. Rapidaptor quick-release technology for rapid bit change. Unlimited torque to loosen seized screws. Multi-component Krafftform handle with hard and soft zones for high working speeds, whilst being easy on the hand. Suitable for bits with 1/4" hexagon head drive as per DIN ISO 1173-C 6.3 and E 6.3 (ISO 1173).

Web link

http://products.wera.de/en/torque_tools_series_7400_krafftform_torque_screwdrivers_pre-set_adjustable_torque_models_7400_vor.html

Wera - 7400 vor
05074716001 - 4013288102928

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Pre-set, adjustable torque screwdrivers



Pre-set torque, adjustable within a defined range. Also available in ESD version (also for HIOS/Halfmoon bits) and with Krafftform Micro handle.

Unlimited torque



Unlimited torque for loosening seized screws.

Versatile




Rapidaptor technology makes the tool adaptable since bits and sockets can be exchanged rapidly.

Rapid-in and self-lock



The bit can be pushed into the adaptor without moving the sleeve. The lock is activated automatically as soon as the bit is applied to the screw. Bits are held securely and wobble-free.

Rapid-out



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. The rapid-out function makes it easy to remove even the smallest bits without extra tools.

Chuck-all



The Rapidaptor quick-release chucks hold 1/4" DIN ISO 1173-C 6,3 and E 6,3 as well as Wera series 1 and 4 bits.

Single-hand function



Every function of the Rapidaptor quick-release chuck, such as inserting or releasing bits, can be carried out with one hand. This is faster, more economical and more ergonomic. There are no unnecessary manoeuvres.

Web link

http://products.wera.de/en/torque_tools_series_7400_krafftform_torque_screwdrivers_pre-set_adjustable_torque_models_7400_vor.html







Wera - 7400 vor
05074716001 - 4013288102928

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

7461 Krafftform pre-set adjustable torque screwdrivers with Rapidaptor quick-release chuck, 1/4 inch, 1,2 Nm
Series 7400 Krafftform Torque Screwdrivers



Further versions in this product family:

								
	art. no.	mm	inch	nm	nm	mm	inch	
	05074790001	7450	89	1/4	0.1	0.1-0.34	133	5 1/4
	05074790010 ¹⁾	7450	89	1/4	0.1	0.1-0.34	133	5 1/4
	05074792001	7451	89	1/4	0.3	0.3-1.0	133	5 1/4
	05074792010 ¹⁾	7451	89	1/4	0.3	0.3-1.0	133	5 1/4
	05074794001	7452	89	1/4	0.9	0.9-1.5	133	5 1/4
	05074794010 ¹⁾	7452	89	1/4	0.9	0.9-1.5	133	5 1/4
	05074715001	7460	105	1/4	0.3	0.3-1.2	155	6
	05074715010 ¹⁾	7460	105	1/4	0.3	0.3-1.2	155	6
	05074716001	7461	105	1/4	1.2	1.2-3.0	155	6
	05074716010 ¹⁾	7461	105	1/4	1.2	1.2-3.0	155	6
	05133177001	7464	105	1/4	3.3	3.0-6.0	155	6

¹⁾ Other pre-set values within the adjustable range can be delivered on request

Web link

http://products.wera.de/en/torque_tools_series_7400_krafftform_torque_screwdrivers_pre-set_adjustable_torque_models_7400_vor.html

Wera - 7400 vor
 05074716001 - 4013288102928

Wera Werkzeuge GmbH
 Korzter Straße 21-25
 D-42349 Wuppertal
 Tel: +49 (0)2 02 / 40 45-0
 E-Mail: info@wera.de