

# TY5232MX



CABLE TIE 18LB 8IN UV BLK 2-PC DIST



## General Information

|                       |   |
|-----------------------|---|
| Extended Product Type | TY5232MX  |
| Product ID            | 7TAG009010R0010   |
| EAN                   | 5414363065302   |
| Catalog Description   | CABLE TIE 18LB 8IN UV BLK 2-PC DIST   |
| Long Description      | Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (220 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 203.2mm (8.0 Inches), Width of 2.54mm (0.10 Inches), Thickness of 1.10mm (0.05 Inches), Tensile Strength Rating of 80 Newtons (18 Pounds), 100 Pack |

## Ordering

|                       |               |
|-----------------------|---------------|
| EAN                   | 5414363065302 |
| Customs Tariff Number | 3926909990    |

## Dimensions

|                    |                   |
|--------------------|-------------------|
| Product Net Weight | .002 lb<br>.907 g |
|--------------------|-------------------|

## Container Information

|                                |                   |
|--------------------------------|-------------------|
| Package Level 1 Units          | 100 piece         |
| Package Level 1 Width          | 5 in<br>127 mm    |
| Package Level 1 Depth / Length | 10.5 in<br>267 mm |
| Package Level 2 Units          | 500 piece         |
| Package Level 2 Width          | 4.1 in<br>104 mm  |
| Package Level 2 Height         | 6.3 in<br>160 mm  |
| Package Level 2 Depth / Length | 9.7 in<br>246 mm  |

## Additional Information

|                 |                               |
|-----------------|-------------------------------|
| Brand / Label   | Ty-Rap                        |
| Bundle Diameter | 0.08 to 1.97 in<br>2 to 50 mm |

|                     |  |
|---------------------|--|
| Color               | Black  |
| Lock Type           | Stainless Steel Barb   |
| Material            | Nylon/Polyamide 6.6  |
| Number of Batteries | 0  |
| Product Name        | Plastic cable tie  |
| Product Type        | Standard   |
| Special Functions   | Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. |
| Surface Finishing   | Untreated  |
| Tensile Strength    | 18 lb<br>80 N  |
| Thickness           | 0.047 in<br>1.1 mm   |
| UPC                 | 786210839370   |

### Certificates and Declarations (Document Number)

|                                   |          |
|-----------------------------------|----------|
| Data Sheet, Technical Information | TY5232MX |
| Instructions and Manuals          | TY5232MX |

### Classifications

|                                    |                           |
|------------------------------------|---------------------------|
| ETIM 6                             | EC000046 - Cable tie      |
| ETIM 7                             | EC000046 - Cable tie      |
| UNSPSC                             | 39121703                  |
| WEEE Category                      | Product Not in WEEE Scope |
| IDEA Granular Category Code (IGCC) | 5034 >> Cable ties        |

### Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

