


Part Number: URM67

COAX URM67 PVC



Product Description

COAX [7x0.75/7.25] URM67 PVC

Technical Specifications

Product Overview

Environmental Space:	Indoor - Euroclass Eca
Suitable Applications:	Coaxial communication cable based on BS2316

Physical Characteristics (Overall)

Conductor

Stranding	Material	Nominal Diameter	No. of Coax
Stranded	BC - Bare Copper	2.25 mm	1
Conductor Count:			1
Conductor Size:			15 AWG

Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	Solid Polyethylene	7.25 mm	0.15 mm

Outer Shield Material

Type	Material	Coverage [%]	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Braid	BC - Bare Copper	92 %	8 mm	0.2 mm	5 %

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
PVC - Polyvinyl Chloride	10.3 mm	0.25 mm
OuterJacket1, Table Note: According the European Standard HD 624		

Electrical Characteristics

Conductor DCR

Inner Conductor DCR	Max. Conductor DCR
6 Ohm/km	6 Ohm/km

Capacitance

Nom. Capacitance	Capacitance Tolerance
98 pF/m	5 pF/m

Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance
50 Ohm	2 Ohm	Min. 40 dB

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
-----------------	---------------------

100 MHz	6.8 dB/100m
200 MHz	9.9 dB/100m
600 MHz	18.6 dB/100m
1000 MHz	25.2 dB/100m

Delay

Nominal Velocity of Propagation (VP) [%]
66 %

Voltage

Voltage Rating [V]
10000 DC / 6500 V RMS

Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-30°C To +70°C
Operating Temp Range:	-30°C To +70°C

Mechanical Characteristics

Min Bend Radius (W/o Pulling Strength):	50 mm
---	-------

Standards

CPR Euroclass:	Eca
Series Type:	UR Series

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	1998-01-01
---------------------------------------	------------

Flammability, LSOH, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1-2
-----------------------	---------------

Part Number

Variants

Item #	Color	Length
URM67.0050	Black	50 m
URM67.00500	Black	500 m

History

Update and Revision:	Revision Number: 0.97 Revision Date: 07-11-2019
----------------------	---

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.