

**machine reamer HM**  
for universal use up to 1300 N/mm<sup>2</sup>



**Application**

for producing H7 fit tolerances in through holes on conventional machines and NC machines up to 1000 N/mm<sup>2</sup>.

**Version**

- 7-8° left-hand spiral and variable pitch, type B

**Advantage**

- good bore hole quality (dimensional tolerance, roundness, surface quality)

| Application | Steel (N/mm <sup>2</sup> ) |       |       | Stainless steel |         | Alu   |      | Brass |      | Bronze |      | Plastics | Graphite G(C)FK | GG(G) GjMW | Titan-alloy | Nickel-alloy | Super-alloy | Hard mat. |         |
|-------------|----------------------------|-------|-------|-----------------|---------|-------|------|-------|------|--------|------|----------|-----------------|------------|-------------|--------------|-------------|-----------|---------|
|             | <700                       | <1000 | <1300 | marten.         | austen. | short | long | short | long | short  | long |          |                 |            |             |              |             | <55 HRC   | <65 HRC |
|             | 18                         | 15    | 12    | 10              | 8       | 20    | 20   | 20    | 20   | 18     | 16   | 18       |                 | 12         | 8           | 8            | 6           |           |         |

|                                |                       |
|--------------------------------|-----------------------|
| <b>Art. No.</b>                | <b>11779 250</b>      |
| <b>Cutting material</b>        | Carbide               |
| <b>Tolerance of fit</b>        | H7                    |
| <b>Groove type</b>             | Left-hand twist, 7-8° |
| <b>Tool holding device</b>     | Morse taper shank     |
| <b>Cutting edge diameter</b>   | 25 mm                 |
| <b>Length</b>                  | 268 mm                |
| <b>Cutting edge length</b>     | 68 mm                 |
| <b>Projecting length</b>       | 169 mm                |
| <b>Morse taper size</b>        | MK 3                  |
| <b>Number of cutting edges</b> | 8 PCS                 |
| <b>f steel 1300</b>            | 0.3 mm/r              |
| <b>DIN</b>                     | 8094                  |

**EAN-Code**

4050293007015