# Rubber Endstop Buffers • low structure 25150.1164



#### **Product Description**

For elastic, damping, and noise-reducing bearings. They also protect the surfaces. The rubber endstop buffers can also be used as spacers and foot ends. Hardness is 70  $\pm$ 5° Shore A.

#### Material


#### Support washer


 Steel, zinc-plated by galvanization, passivated

### Body

• NBR

#### Drawing









#### Order information

| d <sub>1</sub>                | Dimensions   d1 h d2 d3 s1 s2   +0.5 +0.5 +0.5 +0.5 +0.5 +0.5 |   |    |     |     | Spring rate R | Load capacity<br>max. | Spring range | min. | max. | Ĭ   | Art. No.   |
|-------------------------------|---|---|----|-----|-----|---------------|-----------------------|--------------|------|------|-----|------------|
| [mm]                          |   |   |    |     |     | [N/mm]        | [N]                   | [mm]         | [°C] |      | [g] |            |
| with through-bore – picture 1 |   |   |    |     |     |               |                       |              |      |      |     |            |
| 64                            | 5   | 6 | 11 | 2.5 | 1.1 | 1460          | 1460                  | 1            | -30  | 120  | 66  | 25150.1164 |

#### **Application example**





#### Compliance

#### **RoHS compliant**

Contains lead - compliant according to exceptions 6a / 6b / 6c

Contains SVHC substances >0,1% w/w Contains lead - SVHC list [REACH] as of 10.06.2022

#### **Contains Proposition 65 substances**

## 

Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

#### Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.