

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 06.05.2020

Version: 2




Revision: 15.11.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** JENOLITE CHROMESPRAY 400ML
- **Article number:** 89095 & 89295
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 SU21 Consumer uses: Private households / general public / consumers
- **Process category**
 PROC7 Industrial spraying
 PROC11 Non industrial spraying
- **Application of the substance / the mixture** Spray varnish
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Jenolite uk ltd

 Chater Lea Buildings, Icknield Way, Letchworth, Hertfordshire, SG6 1WT
- **Further information obtainable from:** Research & Development: sales@jenolite.net
- **1.4 Emergency telephone number:** During normal business hours: Tel: +1234 924794

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
- | | |
|---|--|
|  | GHS02 flame |
| Aerosol 1 | H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. |
- | | |
|---|---|
|  | GHS08 health hazard |
| STOT RE 2 | H373 May cause damage to organs through prolonged or repeated exposure. |
- | | |
|---|--|
|  | GHS07 |
| Skin Irrit. 2 | H315 Causes skin irritation. |
| Eye Irrit. 2 | H319 Causes serious eye irritation. |
| STOT SE 3 | H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. |
| Asp. Tox. 1 | H304 May be fatal if swallowed and enters airways. |
| Aquatic Chronic 3 | H412 Harmful to aquatic life with long lasting effects. |

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 06.05.2020

Version: 2

Revision: 15.11.2018

Trade name: Chromespray

(Contd. of page 1)

· Hazard pictograms

GHS02 GHS07 GHS08

· Signal word Danger**· Hazard-determining components of labelling:**

Reaction mass of ethylbenzene and xylene

Hydrocarbons, C6-C7, iso-alkanes, cyclic, <5% n-hexane

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

4-methylpentan-2-one

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403 Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures**· Description:** Active substance with propellant**· Dangerous components:**

EC number: 905-588-0 Reg.nr.: 01-2119488216-32 01-2119486136-34	Reaction mass of ethylbenzene and xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	25-<50%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<25%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 06.05.2020

Version: 2

Revision: 15.11.2018

Trade name: Chromespray

(Contd. of page 2)

EC number: 926-605-8 Reg.nr.: 01-2119486291-36	Hydrocarbons, C6-C7, iso-alkanes, cyclic, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	2.5-<10%
CAS: 92128-66-0 EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Consisting of: 110-82-7 cyclohexane (10%); 110-54-3 n-hexane (<5%) Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	2.5-<10%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	2.5-<10%
CAS: 108-10-1 EINECS: 203-550-1 Reg.nr.: 01-2119473980-30	4-methylpentan-2-one Flam. Liq. 2, H225; Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<10%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119486773-24	Solvent naphtha (petroleum), light arom. Benzene<0.1% Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H332; STOT SE 3, H335-H336	1-<2.5%

· **Additional information:**

SECTION 4: First aid measures

· **4.1 Description of first aid measures**· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.· **After eye contact:** Rinse opened eye for several minutes under running water.· **After swallowing:** Do not induce vomiting; call for medical help immediately.· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**· **Suitable extinguishing agents:**

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

· **For safety reasons unsuitable extinguishing agents:** Water with full jet· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.· **5.3 Advice for firefighters**· **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 06.05.2020

Version: 2

Revision: 15.11.2018

Trade name: Chromespray

(Contd. of page 3)

- **6.2 Environmental precautions:**
 - Do not allow product to reach sewage system or any water course.
 - Inform respective authorities in case of seepage into water course or sewage system.
 - Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
 - Dispose contaminated material as waste according to item 13.
 - Ensure adequate ventilation.
 - Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
 - Do not spray onto a naked flame or any incandescent material.
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
 - **Requirements to be met by storerooms and receptacles:**
 - Store in a cool location.
 - Observe official regulations on storing packagings with pressurised containers.
 - **Information about storage in one common storage facility:**
 - Observe official regulations on storing packagings with pressurised containers.
 - **Further information about storage conditions:**
 - Store in cool, dry conditions in well sealed receptacles.
 - Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:	
106-97-8 butane (containing < 0.1% butadiene (203-450-8))	
WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
78-93-3 butanone	
WEL	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV
108-10-1 4-methylpentan-2-one	
WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm Sk, BMGV

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 06.05.2020

Version: 2

Revision: 15.11.2018

Trade name: Chromespray

(Contd. of page 4)

· DNELs		
Reaction mass of ethylbenzene and xylene		
Oral	DNEL Long term-systemic	1.6 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	108 mg/kg bw/day (Consumer)
		180 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local	289 mg/m3 (Worker)
	DNEL Long term-systemic	14.8 mg/m3 (Consumer)
		77 mg/m3 (Worker)
Hydrocarbons, C6-C7, iso-alkanes, cyclic, <5% n-hexane		
Oral	DNEL Long term-systemic	1301 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	1377 mg/kg bw/day (Consumer)
		13964 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	1131 mg/m3 (Consumer)
		5306 mg/m3 (Worker)
92128-66-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
		773 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	608 mg/m3 (Consumer)
		2035 mg/m3 (Worker)
78-93-3 butanone		
Oral	DNEL Long term-systemic	31 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	412 mg/kg bw/day (Consumer)
		1161 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	106 mg/m3 (Consumer)
		600 mg/m3 (Worker)
· PNECs		
Reaction mass of ethylbenzene and xylene		
PNEC Freshwater		0.327 mg/l (Undefined)
PNEC Marine water		0.327 mg/l (Undefined)
PNEC Freshwater sediment		12.46 mg/l(dry weight) (Undefined)
PNEC Soil		2.31 ug/kg (Undefined)
PNEC Sewage Treatment Plant		6.58 mg/l (Undefined)
PNEC Marine water sediment		12.46 mg/l(dry weight) (Undefined)
· Ingredients with biological limit values:		
78-93-3 butanone		
BMGV	70 µmol/L	
	Medium: urine	
	Sampling time: post shift	
	Parameter: butan-2-one	
108-10-1 4-methylpentan-2-one		
BMGV	20 µmol/L	
	Medium: urine	
	Sampling time: post shift	
	Parameter: 4-methylpentan-2-one	

· **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 06.05.2020

Version: 2

Revision: 15.11.2018

Trade name: Chromespray

(Contd. of page 5)

- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing
 - Wash hands before breaks and at the end of work.
 - Do not inhale gases / fumes / aerosols.
 - Avoid contact with the skin.
 - Avoid contact with the eyes and skin.
- **Respiratory protection:**
 - Filter AX/P2
 - Use suitable respiratory protective device in case of insufficient ventilation.
 - Filter A2/P2
- **Protection of hands:**
 - Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm
- **Penetration time of glove material**

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**
 - Safety glasses



Tightly sealed goggles

- **Body protection:** Use protective suit. (EN-13034/6)

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
 - Form:** Liquid
 - Colour:** According to product specification
- **Odour:** Characteristic
- **Odour threshold:** Not determined.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 06.05.2020

Version: 2

Revision: 15.11.2018

Trade name: Chromespray

(Contd. of page 6)

· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	-44.5 °C
· Flash point:	-97 °C
· Flammability (solid, gas):	Not applicable.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.7 Vol %
Upper:	11.5 Vol %
· Vapour pressure at 20 °C:	8300 hPa
· Density at 20 °C:	0.687 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	85.6 %
Solids content:	14.4 %

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

Reaction mass of ethylbenzene and xylene

Oral	LD50	3523 mg/kg (Rat)
Dermal	LD50	12126 mg/kg (Rabbit)
Inhalative	LC50/4 h	29.091 mg/l (Rat)

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 06.05.2020

Version: 2

Revision: 15.11.2018

Trade name: Chromespray

(Contd. of page 7)

Hydrocarbons, C6-C7, iso-alkanes, cyclic, <5% n-hexane		
Inhalative	LC50/4 h	>20 mg/l (Rat)
92128-66-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	LD50	>5840 mg/kg (Rat)
Dermal	LD50	>2920 mg/kg (Rabbit)
Inhalative	LC50 (4h)	>25 mg/l (Rat)
78-93-3 butanone		
Oral	LD50	>2193 mg/kg (Rat)
Dermal	LD50	>5000 mg/kg (Rabbit) 5000 mg/kg (Rabbit)
108-10-1 4-methylpentan-2-one		
Oral	LD50	2100 mg/kg (Rat)
Dermal	LD50	16000 mg/kg (Rabbit)
Inhalative	LC50/4 h	8.3-16.6 mg/l (Rat)
64742-95-6 Solvent naphtha (petroleum), light arom. Benzene<0.1%		
Oral	LD50	>6800 mg/kg (Rat)
Dermal	LD50	>3400 mg/kg (Rabbit)
Inhalative	LC50/4 h	>10.2 mg/l (Rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

Reaction mass of ethylbenzene and xylene	
NOEC	1.3 mg/l (Fish)
NOEC (7 days)	0.96 mg/l (Daphnia magna)
NOEC (72h)	0.44 mg/l (Algae)
NOEC (28 days)	16 mg/l (Bacteria)
LC50 (96h)	8.9-16.4 mg/l (Pimephales promelas)
EC50 (48h)	3.2-9.5 mg/l (Daphnia magna)
Hydrocarbons, C6-C7, iso-alkanes, cyclic, <5% n-hexane	
NOELR (72h)	30 mg/l (Pseudokirchneriella subcapitata)
EL50 (48h)	3 mg/l (Daphnia magna)

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 06.05.2020

Version: 2

Revision: 15.11.2018

Trade name: Chromespray

(Contd. of page 8)

LL50 (96h)	12 mg/l (Onc)
ErC(50) (72h)	55 mg/l (Pseudokirchneriella subcapitata)
EC50	3.78 mg/l (Daphnia magna)
92128-66-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
NOELR (72h)	3 mg/l (Pseudokirchneriella subcapitata)
EL50 (48h)	3 mg/l (Daphnia magna)
EL50 (72h)	30-100 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	11.4 mg/l (Oncorhynchus mykiss)
NOEC (21 days)	0.17 mg/l (Daphnia magna)
LOEC (21 days)	0.32 mg/l (Daphnia magna)
78-93-3 butanone	
LC50 (96h)	2993 mg/l (Pimephales promelas)
EC50 (48h)	308 mg/l (Daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Harmful to fish

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP6	Acute Toxicity
HP14	Ecotoxic

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**

- **ADR, ADN, IMDG, IATA**

UN1950

- **14.2 UN proper shipping name**

- **ADR, ADN**

UN1950 AEROSOLS

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 06.05.2020

Version: 2

Revision: 15.11.2018

Trade name: Chromespray

(Contd. of page 9)

· **IMDG** AEROSOLS
 · **IATA** AEROSOLS, flammable

· **14.3 Transport hazard class(es)**· **ADR**

· **Class** 2.1F Gases.
 · **Label** 2.1

· **ADN**· **ADN/R Class:** 2.1F· **IMDG, IATA**

· **Class** 2.1
 · **Label** 2.1

· **14.4 Packing group**· **ADR, IMDG, IATA** Void· **14.5 Environmental hazards:**· **Marine pollutant:** Yes· **14.6 Special precautions for user**· **Hazard identification number (Kemler code):** -· **EMS Number:** F-D,S-U· **Stowage Code**

Warning: Gases.

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· **Segregation Code**

SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **Transport category**

2

· **Tunnel restriction code**

D

· **IMDG**· **Limited quantities (LQ)**

1L

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 06.05.2020

Version: 2

Revision: 15.11.2018

Trade name: Chromespray

(Contd. of page 10)

- | | |
|-----------------------------------|--|
| · Excepted quantities (EQ) | Code: E0
Not permitted as Excepted Quantity |
| · UN "Model Regulation": | UN 1950 AEROSOLS, 2.1 |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - **Directive 2012/18/EU**
 - **Named dangerous substances - ANNEX I** None of the ingredients is listed.
 - **Seveso category P3a** FLAMMABLE AEROSOLS
 - **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
 - **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
 - **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
 - **National regulations:**
- | Class | Share in % |
|-------|------------|
| II | 2.5-<10 |
| NK | 75-<100 |
- **VOC-CH** 85.55 %
 - **VOC-EU** 587.7 g/l
 - **Danish MAL Code** 5-3
 - **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- **Department issuing SDS:** Research & Development
- **Contact:** ing. J. Sleumer
- **Abbreviations and acronyms:**
- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organisation
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 06.05.2020

Version: 2

Revision: 15.11.2018

Trade name: Chromespray

(Contd. of page 11)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - dermal – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

GB