



Figure similar

**General technical data:**

|  |  |    |
|--|--|----|
| Number of NC contacts for auxiliary contacts       |  | 0  |
| Number of NO contacts for auxiliary contacts       |  | 0  |
| Number of CO contacts for auxiliary contacts       |  | 0  |
| Design of the switching function positively driven |  | No |

**Mechanical data:**

|                                  |    |                      |
|----------------------------------|----|----------------------|
| Type of electrical connection    |    | screw-type terminals |
| Product component Plug-in socket |    | Yes                  |
| Width                            | mm | 15.5                 |

**Certificates/ approvals:**

|                          |       |
|--------------------------|-------|
| General Product Approval | other |
|--------------------------|-------|

[Declaration of Conformity](#)



**Further information**

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrymall>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=LZS:RT17040>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/LZS:RT17040>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)  
[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=LZS:RT17040&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=LZS:RT17040&lang=en)

last modified:

15.01.2015