



Applications

High temperature resistant silicon coated glass braid, ideally suited for use with Class C rated motors and transformers for the winding lead outs and joints as well as additional protection over cables

Properties

Thermal Classification	Class F (155°C)
Construction	Silicone Coated Glass Braid
Maximum Short Term Temperature	450°C
Electric Strength at 20°C	Tested to IEC 684-2 0.8 kV / 1 minute ASTM D350 1.5 kV
Specifications	IEC : 684-3-402 ASTM D-372 Type 4 NEMA VS-1 Grade C2
Flammability	Non-ignitable

Specification Table

Inside Diameter (Minimum)	Wall Thickness (mm)	Length (m)	Colour	Part Number
2	0.4	5	Natural	PP14791
4				PP14792
6	PP14793			
8	PP14794			

This product is Compliant with ROHS 2002 / 95 / EC the restriction of use of certain hazardous substances in electrical and electronic equipment

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.