

Contact Data

Contact Form	: 1 form C
Contact Material	: Ag Alloy
Contact Rating (Resistive)	: 10A 250V AC/30V DC; TV-5
Max. Switching Voltage	: 250V AC/30V DC
Max. Switching Current	: 10A
Max. Switching Power	: 2,500VA, 300W
Min. Switching Load	: 5V DC, 100mA
Max. Contact Resistance	: 100mΩ (6V DC 1A)

Life

Electrical	: 100,000 operations
Mechanical	: 10,000,000 operations

General Data

Min. Insulation Resistance	: 1,000MΩ 500V DC.
Dielectric Strength	: 1,000V AC, 1 min between open contacts 2,500V AC, 1 min between coil and contacts 6,000V AC surge voltage between contact to coil (1.2/50μs)
Operate Time	: Max. 10ms
Release Time	: Max. 5ms
Operate Temperature	: -40°C to +85°C
UL listed	: E326578

Shock Resistance

Endurance	: 1,000m/s ²
Misoperation	: 100m/s ²


Vibration Resistance

Endurance	: 10 to 55Hz, 1.5mm double amplitude
Misoperation	: 10 to 55Hz, 1.5mm double amplitude
Humidity	: 35 to 95%RH, +40°C

Coil Data Chart 20°C

Nominal Voltage V DC	Coil Resistance Ω ±10%	Operate Voltage ≤ V DC	Release Voltage ≥ V DC	Coil Power mW	Insulation Type	Enclosure	Part Number
12	576	8.4	1.2	360	High Insulation	Plastic Sealed Type	MC25113
24	1,600	16.8	2.4				MC25114

Dimensions



Part Number Table

Description	Part Number
Relay	MC25113
	MC25114

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.