

tesaflex® 60760 PV1

Floor Marking Tape

PRODUCT INFORMATION

Product Description

tesaflex® 60760 is a tough plasticized PVC tape coated with an aggressive modified rubber-resin adhesive, which allows adhesion on many different surfaces. tesaflex® 60760 is even tearable by hand.

Main Application

tesaflex® 60760 is perfectly suitable for temporary and low duty hazard warning & marking of any kind of mobile or static objects.

Technical Data

- Backing material
- Total thickness
- Type of adhesive
- soft PVC 150 µm

natural rubber

- Adhesion to steel
- Elongation at break
- 2.5 N/cm 160 %
- Tensile strength
- 28.02 N/cm

Properties

Suitable for rough surfaces

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

Additional Info

tesaflex® 60760 is also available with two highly visible colour-modes which accord to safety-regulations.

For latest information on this product please visit http://l.tesa.com/?ip=60760

Page 1 of 1 / As of 09/29/13

Germany Phone: +49 (40) 4909 101 http://www.tesa.com

tesa tape Asia Pacific Pte. Ltd.

164 Gul Circle, Singapore 629621

Phone: +65 (68) 612 026 Fax: +1 (704) 553 5634 Fax: +65 (68) 614 790 http://www.tesatape.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.