

SPE PCB connector - SPE-T1-M8MRM-90 - 1163795

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




SPE PCB connector, type: IEC 63171-5, degree of protection: IP65/IP67, number of positions: 2, CAT B (ISO/IEC 63171), connection method: THR solder connection, Single Pair Ethernet

Your advantages

- ✔ Connectors in accordance with IEC 63171-5
- ✔ THR solderable
- ✔ Data transmission up to 600 MHz



Key Commercial Data

Packing unit	100 pc
Minimum order quantity	100 pc
GTIN	 4 063151 176136
GTIN	4063151176136
Weight per Piece (excluding packing)	8.180 g
Custom tariff number	85366990
Sales Key	ABNIDA

Technical data

Dimensions

Width	15.2 mm
Height	14.5 mm
Length	31.6 mm

Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 85 °C
Ambient temperature (operation)	-40 °C ... 85 °C
Degree of protection	IP65/IP67 (in combination with M8 housing screw connection)

General

SPE PCB connector - SPE-T1-M8MRM-90 - 1163795

Technical data

General

Number of positions	2
Insulation resistance	> 1 TΩ
Overvoltage category	I
Degree of pollution	2
Connection method	THR solder connection
Transmission characteristics (category)	CAT B (ISO/IEC 63171)
Halogen-free	yes
Resistance to oil	yes
Flame resistance	UL 94 V0
Locking type	Screw locking
Rated voltage (III/2)	72 V DC
Rated current	4 A

Material

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Gold
Contact carrier material	LCP

Cable

Test voltage Core/Core	1000 V DC
Test voltage Core/Shield	2250 V DC
Flame resistance	UL 94 V0
Halogen-free	yes
Resistance to oil	yes

Standards and Regulations

Flame resistance	UL 94 V0
Resistance to oil	yes
Halogen-free	yes
Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 10.0.1	27440390
eCl@ss 11.0	27440390
eCl@ss 9.0	27440402

Accessories

Accessories

Panel mounting base

SPE PCB connector - SPE-T1-M8MRM-90 - 1163795

Accessories

Housing screw connection - SACC-FP-M-M8/M10 SMD - 1412502



M8 pin, front mounting SMD with M10 screw fastening

Housing screw connection - SACC-BP-M-M8/M12 SMD - 1412505



M8 pin, rear mounting
