Solid carbide end mill – fibre glass 4 cutters, diamond-coated



Application

This end mill is suitable for the machining of fibreglass-reinforced plastics, fibreglass, thermoplastics or duroplastic resins, in which fibreglass was introduced as a reinforcement element. The tools are available with left- and right-hand spiral.

Version

- Solid carbide ultra-fine grain
- Diamond coating

• Straight shank in accordance with DIN 6535 HA

Application	Steel (N/mm ²)		Stainless steel		Alu		Brass		Bronze		Plas-						Hard mat.		
	<700	<1000	<1300	marten.	austen.	short	long	short	long	short	long	tics	G(C)FK	GjMW	alloy	alloy	alloy	<55 HRC	<65 HRC
												350							

Art. No.	16658 100				
Cutting material	VHM				
Surface	Diamond coating				
Туре	Right-hand twist				
Number of cutting edges	4 PCS				
Twist angle	30°				
Tool holding device	HA parallel shank				
Overall length	Normal				
Cutting edge diameter	6 mm				
Cutting edge length	19 mm				
Length	76 mm				
Shaft diameter	6 mm				
fz aluminium	0.08 mm				
Overall stainless steel suitability	3				
fitness not iron total	3				
fitness Titan/Nickel/Super total	3				

EAN-Code

4050293434880

