
Spec Sheet

SMD Power Inductors (NR series S type)

NRS4018T2R2MDGJ



Features

- Item Summary 2.2uH±20%, 2.2A, 4.0x4.0x1.8mm
- Lifecycle Stage

Mass Production

Standard packaging quantity (minimum)
Taping Embossed 3500pcs


■ Products characteristics table

Inductance	2.2 uH ± 20 %
Case Size (mm)	4.0x4.0
Rated Current (max)	2.2 A
Saturation Current (max)	3 A
Temperature Rise Current (max)	2.2 A
DC Resistance (typ)	42 mΩ
DC Resistance (max)	50.4 mΩ
LQ Measuring Frequency	100 kHz
Self Resonant Frequency (min)	60 MHz
Operating Temp. Range	-25 to +125 ℃ (Including-self-generated heat)
RoHS2 Compliance	Yes
REACH Compliance	Yes
Soldering	Reflow

External Dimensions

Dimension L	4.0 ±0.2 mm
Dimension W	4.0 ±0.2 mm
Dimension H	Max 1.8 mm
Dimension e	1.1 ±0.2 mm

Recommended Land Patterns



2016.01.25

SMD Power Inductors (NR series S type)

NRS4018T2R2MDGJ

Dimension unit : mm unit: inch Length: 4.0 + / - 0.2(0.157 + / - 0.008)Width: 4.0 +/- 0.2 (0.157 + / - 0.008)max.) Height: 1.8 max. (0.071



Inductance: 2.2 иΗ (test freq at 0.1MHz) DC Resistance: 0.042 / 0.0504 ohm (typ/max)

Saturation Current: 3,000 mA (max) 2,200 mA (max) Temp. rise Current:

> Saturation current typical: 30% reduction from initial L value. Temp rise Current typical: Temperature will rise by 40 deg C

