

5501 Series D Sub Connector




Specifications

Current Rating : 3A AC/DC
 Voltage Rating : 250V AC/DC
 Temperature Range : -55°C to +105°C
 Max. Contact Resistance : 30mΩ
 Min. Insulation Resistance : 5,000MΩ
 Withstand Voltage : 1,000V AC / minute

Materials

Insulator : High temperature plastic
 Contact : Copper Alloy Nickel undercoated, selective gold plated
 Finish : Metal iron with tin plated

Diagram



Dimensions : Millimetres

Part Number	A	B	C	D	E
5501-09PA-02-F1	16.92mm	24.99mm	30.81mm	8.38mm	12.5mm
5501-15PA-02-F1	25.25mm	33.32mm	39.14mm		
5501-25PA-02-F1	38.96mm	47.04mm	53.04mm		
5501-37PA-02-F1	55.42mm	63.5mm	69.32mm		
5501-50PA-02-F1	52.81mm	61.11mm	66.93mm	11.07mm	15.37mm

Part Number Table

Description	Number of Position	Part Number
5501 Series D Sub Connector	9 Way	5501-09PA-02-F1
	15 Way	5501-15PA-02-F1
	25 Way	5501-25PA-02-F1
	37 Way	5501-37PA-02-F1
	50 Way	5501-50PA-02-F1

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
 Farnell.com/multicomp-pro
 Element14.com/multicomp-pro

