

PROFUSION-1

G3A LINE

HEAT PROTECTION

- Handling of hot, wet or oily parts
- Metallurgy, foundry and casting operations
- Thermal treatment operations
- Glass industry: operations on a float furnace



ISO 13997	A	B	C	D	E	F
Cutting load in Newtons	≥ 2	≥ 5	≥ 10	≥ 15	≥ 22	≥ 30

AET N°0075/011/162/03/19/0727 (CTC LYON)

STANDARDS (DETAILS ON WEB SITE)
www.rostaing.com/normes-secureite

SIZES



COMPOSITION

Palm Heat treated cow split leather (glove + cuff)
Back Aluminized fabric
Lining 3XDTECH®
Membrane Porelle®
Total length 45 cm

CARE



PACKAGING

Bag of 5 pairs - Box of 25 pairs

PRO•ONE:
Our selection

PRO•ONE:
Available singly

PRO•CLEAN:
Cleaning option


EXCEPTIONAL
 resistance to
 molten metal spray

Best performances
 for the EN 407
 standard

Adjustable strap




Excellent heat resistance
 Contact heat
 Up to 500 °C
 Heat treated leather



Cut resistance
3XDTECH®
 ROSTAING + 



Forearm protection
 Total length
 45 cm