#### Safety isolating transformer RKD 60/2x15



#### Standards

Safety isolating transformer to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6, UL 5085-1/-2, CSA 22.2 No.66

### Advantages

Minimum size at high power

Low weight

Dual input and dual output voltage for series or parallel connection

Minimal no-load losses

Outstanding temperature behaviour thanks to low magnetic leakage field

## Applications


Very low noise field

As a mains transformer for adjustment of the voltage and simple electrical isolation.

As an isolating transformer for the safe electrical isolation of the input and output sides. The transformer may be used to set up protective separation as a protective measure in accordance with VDE 0100.

As a safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

## Sample application



Series connection (230V): violet with white

SEC:

PRI

Parallel connection: red with gresy/black with orange Series connection: black with grey





UL 5085-1/-2, CSA 22.2 No.66



BLOCK Transformatoren-Elektronik GmbH · Phone +49 4231 678-0 · info@block.eu



# Safety isolating transformer **RKD 60/2x15**

Туре	RKD 60/2x15	Туре	RKD 60/2x15
Input		Fixing method	
Rated input voltage	2 x 115 Vac	Fixing method	Mounting kit, M6 bolt
Rated frequency	50 - 60 Hz	Terminals	Connecting leads, 200 mm
Output		Measures and weights Major diameter Ø	
Rated output voltage	2 x 15 Vac	Major diameter Ø	80 mm
Rated Power	60 VA	Outside diameter in the area of th	e wire lead Ø 83 mm
No-load voltage (app. x factor)	1.14	· e Height without mounting	38 mm
No-load loss (typ.)	0.70 W	😇 Weight	0.75 kg
Efficiency	85.0 %		
Standards		Utside diameter in the area of th Height without mounting Weight	
Classification	Safety isolating transformer		
Approvals			
Approvals	cURus		
Environment			
Ambient temperature max.	40 °C		
Safety and protection			
Туре	Open type		
Insulation class	VDE=B, UL=class 105		
Protection index	IP 00		
Safety class (prepared)	II		
Short circuit strength	non-short-circuit proof		
Test voltage	4,000 Vac, 50 Hz		
Order numbers			
Order Number	RKD 60/2x15		

