

Product information

49 41 A01

Precision Circlip Pliers

For external circlips on shafts DIN 5254 B



- Heavy duty in continuous operation: up to 10 times longer service life • compared to turned tips
- With inserted tips for reliable work •
- With overexpansion guard (adjustable using end stop) •
- Adjustment using hexagonal screw •
- Ideal for series production as excessive expansion of rings is effectively prevented
- Heavy duty under continuous use; up to 10 times longer service life •
- Precise, smoothly-operating screw joint •
- Forged •
- Large contact faces on the tips: no distortion of circlips, easy fitting •
- Slim head style allows use in confined areas •
- Internal opening spring, protected and captive Handles with non-slip plastic coating •
- •
- Angled tips
- With overstretching limiter for standardised assembly in accordance • with DIN 471
- The adjustable stop screw prevents the rings from overstretching
- Inserted tips: spring steel wire, drawn
- Pliers body: chrome vanadium electric steel, forged, oil-hardened

MO**√90**°

General	
Article No.	49 41 A01
EAN	4003773061755
Pliers	grey atramentized
Handles	with non-slip plastic coating
Weight	102 g
Dimensions	130 x 62 x 11 mm
Standard	DIN 5254 B
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Size of shaft	Ø 3 – 10 mm
Tips (diameter)	0.9 mm

technical change and errors excepted

KNIPEX Quality – Made in Germany





Spring inside the joint: the spring is protected inside the precisely bolted joint. It does not hinder work and cannot get dirty or lost.