

# DATA SHEET

Order code	Manufacturer code	Description
85-3623	n/a	n/a

	Page 1 of 2
The enclosed information is believed to be correct, Information may change ±without noticeqdue to product improvement. Users should ensure that the product is suitable for their use. E. & O. E.	Revision A 20/02/2007

Sales: 01206 751166 Sales@rapidelec.co.uk Technical: 01206 835555 Tech@rapidelec.co.uk Fax: 01206 751188 www.rapidonline.com

### FLUKE ®

## 1577/1587 Insulation Multimeters



Fluke 1577



Fluke 1587 Fluke 1587T





#### **Included Accessories**

C101 Rugged, utility hard case TL224 SureGrip Silicone Test Lead Set AC285 SureGrip Alligator Clip Set 80BK Integrated DMM Temperature Probe (Type K)

TP165X Remote Test Probe

#### Ordering Information

Fluke 1577 Insulation Multimeter
Fluke 1587 Insulation Multimeter
Fluke 1587T Insulation Multimeter
Insulation Multimeter
(for Telecom)

10923-eng Rev. 04

#### Two powerful tools in one

The Fluke 1587 and 1577 Insulation Multimeters combine a digital insulation tester with a full-featured True RMS digital multimeter in a single compact, handheld unit, which provides maximum versatility for both troubleshooting and preventive maintenance.

Whether you work on motors, generators, cables, or switch-gear, the Fluke 1587/1577 Insulation Multimeters are ideally suited to help you with your tasks.

The Fluke 1587T is specially designed for the telecom environment.

#### **Features**

Multimeter Features	1577	1587	1587T
True RMS Voltage and Current for accurate measurements	•	•	•
Digital display counts	6000	6000	6000
Autorange and manual range for easy testing.	•	•	•
Selectable filter for accurate voltage and frequency measurements on motor drives		•	•
Min Max Recording, Diode test, temperature, capacitance & frequency measurement for maximum flexibility.		•	•
Insulation features			
User selectable test voltages for many applications	•	•	
Additional test voltages 50V, 100V, 250V		•	
Special remote control probe for easy and safe measurements	•	•	•
Auto-discharge of capacitive voltage for added user protection	•	•	•
Live circuit detection prevents insulation test if voltage $>$ 30V is detected for added user protection	•	•	•
General features			
Auto Power off to save batteries	•	•	•
Large display with backlight	-	•	•
Input Alert to warn for incorrect connections	•	•	•
Continuity	-	•	•

#### **Insulation Specifications**

Functions	1577	1587	1587T
Measurement range	$0.1 \text{M}\Omega$ to $600 \text{M}\Omega$	$0.01 M\Omega$ to $2G\Omega$	0.01MΩ to 100MΩ
Test voltages	500V, 1000V	50V, 100V, 250V, 500V, 1000V	50V, 100V
Test voltage accuracy	+ 20%, - 0%	+ 20%, - 0%	+ 20%, - 0%
Insulation test current	1 mA nominal	1 mA nominal	1 mA nominal
Auto discharge	Discharge time $<$ 0.5s for C = 1 $\mu$ F or less	Discharge time $<$ 0.5s for C =1 $\mu$ F or less	Discharge time < 0.5s for C = 1 µF or less
Maximum capacitive load	Up to 1µF load	Up to 1µF load	Up to 1µF load

#### **Multimeter Specifications**

Functions	Maximum	Max. resolution	1577	1587/1587T
Voltage DC	1000V	1 mV	± (0.2% + 2)	± (0.09% + 2)
Voltage AC	1000V	0.1mV	± (2% + 3)	± (2% + 3)
Current DC	400mA	0.01mA	± (1.0% + 2)	± (0.2% + 2)
Current AC	400mA	0.01mA	± (2% + 2)	± (1.5% + 2)
Resistance	50.0MΩ	0.1Ω	± (1.2% + 2)	± (0.9% + 2)
Capacitance	9999μF	1 nF	-	± (1.2% + 2)
Frequency	99.99kHz	0.01 Hz	-	± (0.1% + 1)
Temperature	-40°C to +537°C	0.1°C	-	± (1% + 10)

Battery life: Meter: 1000 hrs, Insulation Test: >1000 tests

Size (HxWxD):

203 mm x 100 mm x 50 mm

Weight: 0.55 kg Three Year Warranty

#### **Recommended Accessories**











TL238