## ESD Benchtop Mat And Wrist Strap Grounding Kit





## **Specifications:**

Mat:

Construction : Dual layer rubber material

Static Dissipative top layer Conductive rubber bottom layer

Material Thickness : 0.06" ( $\pm 10\%$ ) Dimensions :  $0.078" \times 24" \times 48"$ 

Colour : Grey
Texture : Smooth

Dissipative Colour Side:

RTT: 10E6 - 10E8  $\Omega$  per ANSI/ESD S4.1 RTG: 10E6 - 10E8  $\Omega$  per ANSI/ESD S4.1

"Slows charge removal; meets minimum recommended work surface requirements of ANSI/ESD S20.20 and recommendations of STM 4.1"

Wrist Strap:

Construction : Soft elastic band with silver impregnated polypropylene on the inside for relaible removal of

static charge

Snap : 4mm male stud snap

Cord Length : 6 ft

Cord Terminations : 4mm socket snap, molded banana plug

**Ground Cord:** 

Length : 15 ft

Terminations : 10mm male stud snap, ring terminal

Resistor :  $1m\Omega$ 

**Universal Snap Kit:** 

Size : 10mm

Kit Includes : 10mm stud snap, 10mm socket snap, threaded backing washer, long screw, short screw

and groundable point label

Packaging:

**Tolerances:** 

Product to be packaged with Duratool label

## Part Number Table

Width: ±0.25"

Length: ±0.25" every 1 linear foot of running material

	Description	Part Number
(	Gray, Dual Layer Mat with Adjustable Wrist Strap, Common Point Ground and Universal kit	MC35758

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. DURATOOL is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk www.mcmelectronics.com

