# Radial Leaded Time-Lag Micro Fuse







## **Specification**

Current Rating : 1.25A to 3.15A Voltage Rating : 250V AC

Base and Cover Material : Black Thermoplastic, UL 94-V0

Pins Material : Tin Plated Copper Operating Temperature : -55°C to +125°C

Fuse Size : 8.35mm × 3.95mm × 5mm

# **Interrupting Rating**


35 Amperes or 10 × rated current; whichever is greater at 250V AC 160 amperes at 250V AC 100 amperes at 250V DC

## **Electrical Characteristics**

Rating	150% Rating	210% Rating	275% Rating		400% Rating		1000% Rating	
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
1.25A to 3.15A	600min	2min	400ms	10Sec.	150ms	3Sec	20ms	150ms

Part Number	Ampere Rating (A)	Voltage Rating (V)	Nominal Cold Resistance (Ohms)	Voltage Drop (mV) Max.	Nominal Melting I <sup>2</sup> t (A <sup>2</sup> sec.)
MP000818	1.25		0.0550	130	9.28
MP000819	1.6	250	0.0426	120	17.7
MP000820	2	250	0.0318	100	36
MP000821	3.15		0.0173	100	55.635

### **Mechanical Dimensions**



Dimensions: Millimetres

#### **Part Number Table**

Description	Part Number
Radial Leaded Fuse, Time-Lag, 1.25A, 250V AC	MP000818
Radial Leaded Fuse, Time-Lag, 1.6A, 250V AC	MP000819
Radial Leaded Fuse, Time-Lag, 2A, 250V AC	MP000820
Radial Leaded Fuse, Time-Lag, 3.15A, 250V AC	MP000821

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands Farnell.com/exclusive-brands Element14.com/exclusive-brands

