Screw tap, HSSE M ISO 2 (6H) 0° 376 B for universal use up to 1000 N/mm2



Application

For producing metric threads on CNC machines or conventional machines in **through holes** in the steel, (stainless steel), non-ferrous metals and (cast iron) material groups up to a strength of 1000 N/mm².

Version

with over-long shank

Advantage

good service life and process reliability thanks to innovative cutting geometry and universal use for the greatest flexibility in applications

Application	Steel (N/mm ²)			Stainless steel		Alu		Brass		Bronze		Plas-			Titan-		Super-	Hard mat.	
	<700	<1000	<1300	marten.	austen.	short	long	short	long	short	long	tics	G(C)FK	GjŴŴ	alloy	alloy	alloy	<55 HRC	<65 HRC
	16	11		9		18	18	15	18	15	15	13		16					

Art. No.	13117 220					
Туре	P MAX 1000					
Thread type	Metric thread					
Thread type x nominal diameter	M22					
Pitch	2.5 mm					
Hole type	Clearance hole $\leq 3xD$					
Cutting material	HSSE					
Surface	Vaporised					
Lead angle shape	В					
Tolerance of screw taps	ISO 2 (6H)					
Twist angle	0°					
Shaft diameter	18 mm					
Application type/machine type	CNC, Conventional					
Core hole diameter	19.5 mm					
Coolant supply	External					
Length	140 mm					
Shank square	14.5 mm					
Cutting speed (steel 1000) suitability	1					
Cutting speed (steel 1300) suitability	3					
Overall stainless steel suitability	3					
fitness not iron total	1					
fitness Titan/Nickel/Super total	3					
Cutting speed (cast) suitability	2					
Cutting speed (hard 55) suitability	3					
Cutting speed (hard 65) suitability	3					
DIN	376					

EAN-Code

4050293017694

