# Pluggable Terminal Block
## 3.5mm Pitch

**multicomp**PRO

## Features

- Vertical header
- Closed ends

## Specifications

| | |
|---|---|
| Rated Voltage | : 150V AC |
| Rated Current | : 12A |
| Housing Material | : Polyamide 66 |
| Solder Pin | : 0.8mm, brass, tin plated |
| Operating Temperature | : -40°C to +105°C |
| PCB Hole Diameter | : Ø1.3mm |

## Diagram



Dimensions : Millimetres (Inches)

## Part Number Explanation

MCT    E  -  04    A    02

| | |
|---|---|
| MCT | Multicomp Terminal Blocks |
| E | Pluggable Type (Header Side) |
| 04 | Series |
| A | Pitch Size |
| 02 | Number of Positions |

Pitch Size        : A = 3.5mm

Number of Positions : 02 = 2, 03 = 3, 04 = 4, 05 = 5, 06 = 6, 07 = 7, 08 = 8, 09 = 9, 10 = 10, 11 = 11 and 12 = 12 Positions

## Part Number Table

| Description | A (mm) | A (Inch) | Part Number |
|---|---|---|---|
| Pluggable Terminal Block-Vertical Header / Closed Ends / 3.5mm Pitch | 7.6 | 0.299 | MCTE-04A02 |
| | 11.1 | 0.437 | MCTE-04A03 |
| | 14.6 | 0.575 | MCTE-04A04 |
| | 18.1 | 0.713 | MCTE-04A05 |
| | 21.6 | 0.85 | MCTE-04A06 |
| | 25.1 | 0.988 | MCTE-04A07 |
| | 28.6 | 1.126 | MCTE-04A08 |
| | 32.1 | 1.264 | MCTE-04A09 |
| | 35.6 | 1.402 | MCTE-04A10 |
| | 39.1 | 1.539 | MCTE-04A11 |
| | 42.6 | 1.677 | MCTE-04A12 |

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

**multicomp**PRO

Page <1>                                                                 07/05/20   V1.0