# **Rubber Endstop Buffers** • low structure

25150.1126



# **Product Description**

For elastic, damping, and noise-reducing bearings. They also protect the surfaces. The rubber endstop buffers can also be used as spacers and foot ends. Hardness is 70  $\pm 5^{\circ}$  Shore A.

#### **Material**


#### Support washer

Steel, zinc-plated by galvanization, passivated


#### **Body**

• NBR

## **Drawing**



picture 1




picture 2


#### Order information

Dimensions						Spring rate R	Load capacity	Spring range			I	Art. No.
d <sub>1</sub>	h	<b>d</b> <sub>2</sub> +0.5	<b>d</b> <sub>3</sub> +0.5	s <sub>1</sub>	S <sub>2</sub>		max.		min.	max.		
[mm]						[N/mm]	[N]	[mm]	[°C]		[g]	
with through-bore – picture 1												
25	8	4	7.5	1.5	1.1	349	698	2	-30	120	8	25150.1126

## **Application example**



Erwin Halder KG





www.halder.com Page 1 of 2
Published on: 8.7.2022

## Compliance

## **RoHS** compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c

#### Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 10.06.2022

#### **Contains Proposition 65 substances**



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

#### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Erwin Halder KG

Page 2 of 2 www.halder.com

Published on: 8.7.2022