
## MTi-610

- Small, IP 51 rated IMU
- Factory calibrated inertial data
- Full GUI and SDK available

The MTi-610 is a Inertial Measurement Unit with a small form-factor design for deep integration into your application. Building on the proven MTi 600-series technology it enables a robust and easy to use motion tracking. It is designed for easy integration and seamless interfacing with other equipment.

The MTi-610 is supported by the MT Software Suite which includes MT Manager (GUI for Windows/Linux), SDK, example codes and drivers for many platforms.



## **IMU** performance

INO performance	
Accelerometer	Calibrated
Gyroscope	Calibrated
Strapdown Integration (SDI)	Yes
Gyroscope	
Standard full range	2000 deg/s
In-run bias stability	8 deg/h
Bandwidth (-3dB)	520 Hz
Noise Density	0.007 º/s/√Hz
g-sensitivity (calibr.)	0.001 º/s/g
Accelerometer	
Standard full range	10 g
In-run bias stability	10 (x,y) 15(z) µg
Bandwidth (-3dB)	500 Hz
Noise Density	60 µg/√Hz
Magnetometer	
Standard full range	+/- 8 G
Total RMS noise	1 mG
Non-linearity	0.2%
Resolution	0.25 mG
GNSS Receiver	
Brand	n/a
Model	n/a
RTCM input port	n/a
Barometer	
Standard full range	300-1250 hPa
Total RMS noise	1.2 Pa
Relative accuracy	+/- 8 Pa (~0.5m)

Mechanical		
IP-rating Operating Temperature Casing material Mounting orientation Dimensions Connector	<ul> <li>IP51</li> <li>-40 to 85 °C</li> <li>PC-ABS</li> <li>No restriction, full 360° in all axes</li> <li>28x31.50x13 mm</li> <li>Main: Phoenix Contact 16 pin, 1.27 mm pitch</li> </ul>	
Weight	8.9 g	
Electrical		
Input voltage Power consumption (typ)	- 4.5 to 24V <1 W	
Interfaces / IO		
Interfaces Sync Options Protocols Clock drift Output Frequency Built-in-self test	<ul> <li>UART, CAN, RS232</li> <li>SyncIn, SyncOut, ClockSync</li> <li>Xbus, ASCII (NMEA) or CAN</li> <li>10 ppm (or external)</li> <li>2 kHz, 400 Hz SDI</li> <li>Yes</li> </ul>	
Software Suite		
GUI (Windows/Linux)	<ul> <li>MT Manager Firmware updater,</li> <li>Magnetic Field Mapper</li> <li>C++, C#, python, Matlab, Nucleo,</li> <li>public source code</li> </ul>	
Drivers Support	<ul> <li>LabVIEW, ROS, GO</li> <li>BASE by XSENS: online manuals, community and knowledge base</li> </ul>	
White label and OEM integration options available     D models available on request		

• 3D models available on request

• Available online via Digi-Key, Mouser, Farnell and local distributors



© Xsens, March 2021