# Seating Pins ⋅ pin shape 22680.0438




# **Product Description**


To be used as solid and precise seat and stop. The pin-shaped form of this locating pin allows an application in components with narrow seating points.
Bearing surface induction hardened and grounded.

• Heat-treated steel, tempered, blackened

# **Drawing**










picture 1


picture 2


# **Order information**


Dimensions						WS	Tightening torque	I	Art. No.
I <sub>1</sub>	d <sub>1</sub>	d <sub>2</sub>	l <sub>2</sub>	l <sub>3</sub>	d <sub>3</sub>		max.	_	
±0.01									
[mm]						F 7	FA11	F7	
			[mm]			[mm]	[Nm]	[g]	
with male th	read – picture 1		[mm]			[mm]	[NM]	[9]	

# **Application example**









# Compliance

# **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863

#### Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 10.06.2022

Erwin Halder KG

### **Does not contain Proposition 65 substances**

No Proposition 65 substances included https://www.P65Warnings.ca.gov/

### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halder.com Page 2 of 2

Published on: 8.7.2022