# 9 Way DTE Type Serial Plug to Socket Lead






# RoHS Compliant

## **Specifications**

Connector Type A : D Subminiature Plug, 9 Way
Connector Type B : D Subminiature Socket, 9 Way

 $\begin{array}{lll} \mbox{Conductor Resistance} & : 3\Omega \mbox{ Max.} \\ \mbox{Insulation Resistance} & : 10M\Omega \mbox{ Min.} \\ \mbox{Jacket Colour} & : \mbox{Beige} \\ \end{array}$ 

## Diagram





#### Notes:

### **Materials**

1. Cable: 7/0.10BCx9C+D(7/0.10BC)+AM+ Grey PVC Jacket. OD = Ø5.4 ±0.2mm.

Cable Marking: Computer Interface Cable 300V 80°C

- 2. Connector: P1: DB9 Type Male: Solder Type, Blue PBT Insulation, Gold Flash Contacts, Nickel Plated Shell.
- 3. Connector: P2: DB9 Type Female: Solder Type, Blue PBT Insulation, Gold Flash Contacts, Nickel Plated Shell.
- 4. Hood Molded Cold Grey PVC
- 5. Thumb Screw to be Molded Grey PVC

## **Part Number Table**

Description	"L"	Part Number
9 Way DTE Type Serial Plug to Socket Lead	2000 ±50mm	PSG90632

Dimensions: Millimetres

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-SIGNAL is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands Farnell.com/exclusive-brands Element14.com/exclusive-brands

