

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15
- 16
- 17
- 18

MATERIAL

Zinc-plated steel insert.

NO-SLIP COATING

Thermoplastic elastomer (TPE), hardness 80 shore A.

STANDARD EXECUTION

(NdFeB) Neodymium-iron-boron retaining magnet, for temperatures up to 80°C.

- **RMG-ND-BK**: with no-slip coating in RAL 9011 black colour.
- **RMG-ND-WT**: with no-slip coating in RAL 9016 white colour.
- **RMI-ND-BK**: with no-slip coating in RAL 9011 black colour.
- **RMI-ND-WT**: with no-slip coating in RAL 9016 white colour.

Retaining magnets technical data (on page 756).

FEATURES AND APPLICATIONS

RMG-RMI flat retaining magnets are shielded magnetic systems with high performances and moderate overall dimensions.

The elastomer surface increases the friction coefficient when lateral retaining forces are present, giving a better adhesion. These magnets are preferably used for sensitive surfaces.







RMG-ND (D=22 / 43 / 66 / 88)


RMG-ND (D=31)

RMI-ND (D=22 / 57 / 66)


RMI-ND (D=31)



View on A



View on B



RMG-ND-BK

RMG-ND-WT

Code	Description	Code	Description	D	d	L	h	h1	Nominal adhesive forces* [N]	⚖️
501596	RMG-ND-18-BK	501597	RMG-ND-18-WT	18	M4	6	4.5	1	38	6
501601	RMG-ND-22-BK	501603	RMG-ND-22-WT	22	M4	6	4.5	0.8	38	9
501611	RMG-ND-31-BK	501613	RMG-ND-31-WT	31	M5	6	4.5	0.8	89	21
501621	RMG-ND-43-BK	501623	RMG-ND-43-WT	43	M4	6	4.5	0.8	100	29
501626	RMG-ND-57-BK	501627	RMG-ND-57-WT	57	M5	7.6	5.7	1.4	38	79
501631	RMG-ND-66-BK	501633	RMG-ND-66-WT	66	M6	8.5	6	1.8	250	100
501641	RMG-ND-88-BK	501643	RMG-ND-88-WT	88	M6	8.5	6	1.8	550	186

RMI-ND-BK

RMI-ND-WT

Code	Description	Code	Description	D	d	L	h	d1	Nominal adhesive forces* [N]	⚖️
501791	RMI-ND-18-BK	501793	RMI-ND-18-WT	18	3	6	3	8	38	5
501801	RMI-ND-22-BK	501803	RMI-ND-22-WT	22	4	6	3.5	8.2	38	8
501811	RMI-ND-31-BK	501813	RMI-ND-31-WT	31	6	6	3.5	9	89	20
501821	RMI-ND-57-BK	501823	RMI-ND-57-WT	57	8	7.5	3.5	25.3	175	77
501831	RMI-ND-66-BK	501833	RMI-ND-66-WT	66	5.5	8.5	3.5	25	250	100

Industrial magnets

* The values of the nominal adhesive forces are approximate and refer to magnetic properties observed on laboratory samples.