Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

WD-40® Bike® All Conditions Lube WD-40® Specialist® Bike® All Conditions Lube

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

WD-40 Company Limited PO Box 440 GB-Kiln Farm, Milton Keynes, MK11 3LF

Tel.: +44 (0) 1908 555400 Fax: +44 (0) 1908 266900 E-Mail: Compliance@wd40.co.uk Homepage: www.wd40.co.uk

(RL)

Euro Car Parts Team P. R. Reilly Unit K Furry Park Industrial Est. Swords Road Turnapin Little Dublin 9 D09 TC1

Email: custservice.ie@eurocarparts.com Phone: 1800 818 440

Danka Import Export 548 St Joseph High Road SVR 1018 St Venera

Tel.: +356 21233649 Fax: +356 21233501 E-Mail: Danka@maltanet.net

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Medicines & Poisons Info Office - Mater Dei Hospital, Msida MSD 2090, Malta - Tel.: 2545 6508 Emergency Ambulance - Tel.: 112 (B) (RL) (M) Page 2 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.11.2020 / 0012 Replacing version dated / version: 10.11.2020 / 0011 Valid from: 30.11.2020 PDF print date: 02.12.2020 WD-40® Bike® All Conditions Lube WD-40® Specialist® Bike® All Conditions Lube

Medicines & Poisons Info Office - Mater Dei Hospital, Msida MSD 2090, Malta - Tel.: 2545 6508 Emergency Ambulance - Tel.: 112 (IRL)

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.: +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week) +353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (WDC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP) Hazard class Hazard category Hazard statement Asp. Tox. 1 H304-May be fatal if swallowed and enters airways. STOT SE 3 H336-May cause drowsiness or dizziness. 1 Aerosol H222-Extremely flammable aerosol.

H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

1



Danger

Aerosol

H336-May cause drowsiness or dizziness. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking. EUH208-Contains Benzene, mono-C10-13-alkyl derivatives, distillation residues, sulfonated, sodium salts, Benzene, mono-C10-13alkyl derivatives, distillation residues, sulfonated, barium salts. May produce an allergic reaction.

Without adequate ventilation, formation of explosive mixtures may be possible. Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Hydrocarbons, C6, isoalkanes, <5% n-hexane Baseoil - unspecified

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol 3.1 Substances

n.a. **3.2 Mixtures**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2%	
aromatics	
Registration number (REACH)	01-2119463258-33-XXXX
Index	
EINECS, ELINCS, NLP	919-857-5 (REACH-IT List-No.)
CAS	
content %	40-60
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226
	Asp. Tox. 1, H304
	STOT SE 3 H336

Baseoil - unspecified *	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	
content %	20-30
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

2-(2-butoxyethoxy)ethanol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475104-44-XXXX
Index	603-096-00-8
EINECS, ELINCS, NLP	203-961-6
CAS	112-34-5
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Irrit. 2, H319

Hydrocarbons, C6, isoalkanes, <5% n-hexane	
Registration number (REACH)	01-2119484651-34-XXXX
Index	
EINECS, ELINCS, NLP	931-254-9 (REACH-IT List-No.)
CAS	(64742-49-0)
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225
	Asp. Tox. 1, H304
	Skin Irrit. 2, H315
	STOT SE 3, H336

Aquatic Chronic 2, H411

Benzene, mono-C10-13-alkyl derivatives, distillation residues,	
sulfonated, sodium salts	
Registration number (REACH)	01-2120138372-62-XXXX
Index	
EINECS, ELINCS, NLP	944-207-2 (REACH-IT List-No.)
CAS	
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315
	Skin Sens, 1B, H317

Benzene, mono-C10-13-alkyl derivatives, distillation residues, sulfonated, barium salts	
Registration number (REACH)	01-2120767409-42-XXXX
Index	
EINECS, ELINCS, NLP	947-582-0 (REACH-IT List-No.)
CAS	
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Sens. 1B, H317

Impurities, test data and additional information may have been taken into account in classifying and labelling the product. For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

* The contained mineral oil ca	In be described by one or more of t	he following numbers:
EINECS, ELINCS, NLP	Registration number	Chemical name
	(REACH)	
265-169-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic
265-157-1	01-2119484627-25-XXXX	Distillates (petroleum), hydrotreated heavy paraffinic
265-156-6	01-2119480375-34-XXXX	Distillates (petroleum), hydrotreated light naphthenic
265-158-7	01-2119487077-29-XXXX	Distillates (petroleum), hydrotreated light paraffinic
232-455-8	01-2119487078-27-XXXX	White mineral oil (Natural oil)
276-738-4	01-2119474889-13-XXXX	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-
		based
500-183-1 (NLP)	01-2119486452-34-XXXX	1-Decene, homopolymer, hydrogenated
276-737-9	01-2119474878-16-XXXX	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-
		based
265-159-2	01-2119480132-48-XXXX	Distillates (petroleum), solvent-dewaxed light paraffinic
482-220-0	01-0000020163-82-XXXX	C18-C50 branched, cyclic and linear hydrocarbons - Distillates

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

At high concentrations: Irritation of the respiratory tract Coughing Dizziness Headaches Effect on the central nervous system Coordination disorders

Unconsciousness

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

Page 5 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.11.2020 / 0012 Replacing version dated / version: 10.11.2020 / 0011 Valid from: 30.11.2020 PDF print date: 02.12.2020 WD-40® Bike® All Conditions Lube WD-40® Specialist® Bike® All Conditions Lube

5.1 Extinguishing media Suitable extinguishing media

CO2 Extinction powder Water jet spray Large fire: Water jet spray / alcohol resistant foam Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Toxic gases Danger of bursting (explosion) when heated Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available. Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Page 6 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.11.2020 / 0012 Replacing version dated / version: 10.11.2020 / 0011 Valid from: 30.11.2020 PDF print date: 02.12.2020 WD-40® Bike® All Conditions Lube

____

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals. Store product closed and only in original packing. Not to be stored in gangways or stair wells. Do not store with oxidizing agents. Observe special regulations for aerosols! Observe special storage conditions. Keep protected from direct sunlight and temperatures over 50°C. Store in a well ventilated place.

WD-40® Specialist® Bike® All Conditions Lube

7.3 Specific end use(s)

(BR) (M)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cy	clics, <2% aromatics/		60
WEL-TWA: 800 mg/m3	WEL-STEL:			
Monitoring procedures:	 Draeger - Hydrocarbons 0,1%/c Draeger - Hydrocarbons 2/a (81 Compur - KITA-187 S (551 174) 	03 581)		
BMGV:		Other information: (0 method, paragraphs 8		:. to RCP- H40)
Chemical Name	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cy	clics, <2% aromatics		Content %:40- 60
OELV-8h: 100 ppm (573 mg/m3 solvent", [White spirit])				
Monitoring procedures:	 Draeger - Hydrocarbons 0,1%/c Draeger - Hydrocarbons 2/a (81 Compur - KITA-187 S (551 174) 	03 581)		
BLV:		Other information:		
Chemical Name	2-(2-butoxyethoxy)ethanol			Content %:1-5
WEL-TWA: 10 ppm (67,5 mg/m	3) (WEL, EU) WEL-STEL: 15 ppm (101,2	mg/m3) (WEL, EU)		
Monitoring procedures:				
BMGV:		Other information:	-	
Chemical Name	2-(2-butoxyethoxy)ethanol			Content %:1-5
OELV-8h: 10 ppm (67,5 mg/m3) (OELV, EU) OELV-15min: 15 ppm (101,	2 mg/m3) (OELV, EU)		
Monitoring procedures: BLV:		Other information: IC	OELV	
	2 (2 hutowysthewy) othered		0221	Content 0/11 E
Chemical Name OELV-8h: 10 ppm (67,5 mg/m3	2-(2-butoxyethoxy)ethanol) (OELV-8h, UE) OELV-ST: 15 ppm (101,2 m	a/m3) (OEL \/-ST		Content %:1-5
		Ig/III3) (OLLV-01,		
Monitoring procedures: BMGV:		Other information		
		Other information:	-	-
Chemical Name	Hydrocarbons, C6, isoalkanes, <5% n-hexane			Content %:1- <2,5
WEL-TWA: 800 mg/m3	WEL-STEL:	(04.00.574)		
Monitoring procedures:	 Draeger - Hydrocarbons 0,1%/c Draeger - Hydrocarbons 2/a (81 			
	- Compur - KITA-187 S (551 174)	03 301)		
BMGV:		Other information: (0 method, paragraphs 8		:. to RCP- H40)
Chemical Name	Hydrocarbons, C6, isoalkanes, <5% n-hexane			Content %:1- <2,5
OELV-8h: 100 ppm (573 mg/m3 solvent", [White spirit])	B) ("Stoddard OELV-15min:			

Page 7 of 19 Safety data sheet according						
Revision date / version: 30.1 Replacing version dated / ver Valid from: 30.11.2020 PDF print date: 02.12.2020 WD-40® Bike® All Condition WD-40® Specialist® Bike®	ersion: 10.11.2020 / 0011 ns Lube	/2006, Annex II				
Monitoring procedures:	- Drae	ger - Hydrocarbons 0,1% ger - Hydrocarbons 2/a (8 our - KITA-187 S (551 17-	31 03 581) 4)			
BLV:			Other infor	rmation:		
Chemical Name WEL-TWA: 5 mg/m3 (Mine metal working fluids, ACGIH		EL-STEL:				Content %:
Monitoring procedures: BMGV:		ger - Oil Mist 1/a (67 33 0	31) Other infor	rmation:		
Chemical Name	Oil mist, mineral				-	Content %:
OELV-8h: 5 mg/m3 (Miner severely refined (inhalable)) Monitoring procedures:		ELV-15min: ger - Oil Mist 1/a (67 33 0	31)			
BLV:	Dido		Other info	rmation:		
Chemical Name	Petroleum gases, liqu	efied				Content %:
WEL-TWA: 1000 ppm (17) petroleum gas (LPG))	50 mg/m3) (Liquefied W	EL-STEL: 1250 ppm (2 troleum gas (LPG))	180 mg/m3) (L	iquefied		
Monitoring procedures: BMGV:			Other info	mation.		
Chemical Name	Petroleum gases, liqu	efied				Content %:
OELV-8h:		ELV-15min: 1000 ppm (Butane)			Contone 70.
Monitoring procedures: BLV:			Oth an infe			
DLV			Other info	mation.		
Hvdrocarbons. C9-C11. n-	alkanes, isoalkanes, cyclic	s. <2% aromatics				
Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental compartment		r			
Canaumar	compartment					
Consumer	Human - oral	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Consumer	Human - oral Human - dermal	effects Long term, systemic	DNEL DNEL	300 300	bw/day mg/kg	
		effects Long term, systemic effects Long term, systemic			bw/day	
Consumer	Human - dermal	effects Long term, systemic effects Long term, systemic effects Long term, systemic	DNEL	300	bw/day mg/kg bw/day mg/m3 mg/kg	
Consumer	Human - dermal Human - inhalation	effects Long term, systemic	DNEL	300 900	bw/day mg/kg bw/day mg/m3	
Consumer Consumer Consumer Consumer Consumer	Human - dermal Human - inhalation Human - dermal Human - inhalation Human - oral	effects Long term, systemic effects	DNEL DNEL DNEL DNEL DNEL	300 900 125 185 125	bw/day mg/kg bw/day mg/m3 mg/kg bw/day mg/m3 mg/kg bw/day	
Consumer Consumer Consumer Consumer Consumer Workers / employees	Human - dermal Human - inhalation Human - dermal Human - inhalation Human - oral Human - dermal	effects Long term, systemic effects	DNEL DNEL DNEL DNEL DNEL DNEL	300 900 125 185 125 300	bw/day mg/kg bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/kg bw/day	
Consumer Consumer Consumer Consumer Consumer Workers / employees Workers / employees	Human - dermal Human - inhalation Human - dermal Human - inhalation Human - oral Human - dermal Human - inhalation	effects Long term, systemic effects	DNEL DNEL DNEL DNEL DNEL DNEL DNEL	300 900 125 185 125	bw/day mg/kg bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/kg bw/day mg/kg	
Consumer Consumer Consumer Consumer Consumer Workers / employees Workers / employees Workers / employees	Human - dermal Human - inhalation Human - dermal Human - inhalation Human - oral Human - dermal Human - inhalation Human - dermal	effects Long term, systemic effects	DNEL DNEL DNEL DNEL DNEL DNEL DNEL DNEL	300 900 125 185 125 300 1500 208	bw/day mg/kg bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/kg bw/day mg/m3 mg/kg bw/day	
Consumer Consumer Consumer Consumer Consumer Workers / employees Workers / employees	Human - dermal Human - inhalation Human - dermal Human - inhalation Human - oral Human - dermal Human - inhalation	effects Long term, systemic	DNEL DNEL DNEL DNEL DNEL DNEL DNEL	300 900 125 185 125 300 1500	bw/day mg/kg bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/kg bw/day mg/kg bw/day	
Consumer Consumer Consumer Consumer Consumer Workers / employees Workers / employees Workers / employees Workers / employees	Human - dermal Human - inhalation Human - dermal Human - inhalation Human - oral Human - dermal Human - inhalation Human - dermal Human - inhalation	effects Long term, systemic	DNEL DNEL DNEL DNEL DNEL DNEL DNEL DNEL	300 900 125 185 125 300 1500 208	bw/day mg/kg bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/kg bw/day mg/m3 mg/kg bw/day	
Consumer Consumer Consumer Consumer Consumer Workers / employees Workers / employees Workers / employees	Human - dermal Human - inhalation Human - dermal Human - inhalation Human - oral Human - dermal Human - inhalation Human - dermal Human - inhalation	effects Long term, systemic	DNEL DNEL DNEL DNEL DNEL DNEL DNEL DNEL	300 900 125 185 125 300 1500 208	bw/day mg/kg bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/kg bw/day mg/m3 mg/kg bw/day	Note
Consumer Consumer Consumer Consumer Consumer Workers / employees Workers / employees Workers / employees Workers / employees 2-(2-butoxyethoxy)ethano	Human - dermal Human - inhalation Human - dermal Human - inhalation Human - oral Human - dermal Human - dermal Human - dermal Human - inhalation Human - inhalation Human - inhalation Human - inhalation Exposure route / Environmental compartment Environment - freshwater	effects Long term, systemic effects	DNEL DNEL DNEL DNEL DNEL DNEL DNEL DNEL	300 900 125 185 125 300 1500 208 871 Value 1,1	bw/day mg/kg bw/day mg/m3 mg/kg bw/day mg/m3 mg/kg bw/day mg/m3 mg/kg bw/day mg/m3	Note
Consumer Consumer Consumer Consumer Consumer Workers / employees Workers / employees Workers / employees Workers / employees 2-(2-butoxyethoxy)ethano	Human - dermal Human - inhalation Human - dermal Human - inhalation Human - oral Human - dermal Human - dermal Human - dermal Human - inhalation Exposure route / Environmental compartment Environment - freshwater Environment - marine	effects Long term, systemic effects	DNEL DNEL DNEL DNEL DNEL DNEL DNEL DNEL	300 900 125 185 125 300 1500 208 871 Value 1,1 0,11	bw/day mg/kg bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/m3 mg/kg bw/day mg/m3	Note
Consumer Consumer Consumer Consumer Consumer Workers / employees Workers / employees Workers / employees Workers / employees 2-(2-butoxyethoxy)ethano	Human - dermal Human - inhalation Human - dermal Human - inhalation Human - oral Human - dermal Human - dermal Human - dermal Human - inhalation Human - inhalation Human - inhalation Human - inhalation Exposure route / Environmental compartment Environment - freshwater	effects Long term, systemic effects	DNEL DNEL DNEL DNEL DNEL DNEL DNEL DNEL	300 900 125 185 125 300 1500 208 871 Value 1,1	bw/day mg/kg bw/day mg/m3 mg/kg bw/day mg/m3 mg/kg bw/day mg/m3 mg/kg bw/day mg/m3	Note
Consumer Consumer Consumer Consumer Consumer Workers / employees Workers / employees Workers / employees Workers / employees 2-(2-butoxyethoxy)ethano	Human - dermal Human - inhalation Human - dermal Human - inhalation Human - oral Human - dermal Human - dermal Human - inhalation Human - dermal Human - inhalation Human - dermal Human - inhalation Human - inhalation Exposure route / Environmental compartment Environment - freshwater Environment - marine Environment - water, sporadic (intermittent)	effects Long term, systemic effects	DNEL DNEL DNEL DNEL DNEL DNEL DNEL DNEL	300 900 125 185 125 300 1500 208 871 Value 1,1 0,11	bw/day mg/kg bw/day mg/m3 mg/kg bw/day mg/kg bw/day mg/m3 mg/kg bw/day mg/m3	Note

	Environment - sediment, marine		PNEC	0,44	mg/kg
	Environment - soil		PNEC	0,32	mg/kg
	Environment - sewage treatment plant		PNEC	200	mg/l
	Environment - oral (animal feed)		PNEC	56	mg/kg
Consumer	Human - inhalation	Short term, local effects	DNEL	60,7	mg/m3
Consumer	Human - dermal	Long term, systemic effects	DNEL	50	mg/kg bw/d
Consumer	Human - inhalation	Long term, systemic effects	DNEL	40,5	mg/m3
Consumer	Human - oral	Long term, systemic effects	DNEL	5	mg/kg bw/d
Consumer	Human - inhalation	Long term, local effects	DNEL	40,5	mg/m3
Workers / employees	Human - oral	Long term, local effects	DNEL	67,5	mg/m3
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	89	mg/kg bw/d
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	83	mg/kg bw/d
Workers / employees	Human - inhalation	Short term, local effects	DNEL	101,2	mg/m3
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	67,5	mg/m3

Hydrocarbons, C6, isoa	lkanes, <5% n-hexane					
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	1301	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1377	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1131	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	13964	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5306	mg/m3	

^(B) WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |

OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) =

(B) (M)
 Page 9 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 30.11.2020 / 0012
 Replacing version dated / version: 10.11.2020 / 0011
 Valid from: 30.11.2020
 PDF print date: 02.12.2020
 WD-40® Bike® All Conditions Lube
 WD-40® Specialist® Bike® All Conditions Lube

Inhalable Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU. (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BLV = Biological limit value |

Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

© OELV-8h = Occupational Exposure Limit Value - 8 h (8-hour reference period as a time-weighted average)

[9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |

OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period)

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).

[8] = Short-term exposure limit value in relation to a reference period of 1 minute. (S.L.424.24), [9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24) |

BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Skin = Possibility of a significant uptake through the skin.

[11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. (S.L.424.24), [12] = The mist is defined as the thoracic fraction. (S.L.424.24), [13] = Established in accordance with the Annex to Directive 91/322/EEC. (S.L.424.24), [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV. (S.L.424.24).

(EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and nonmetrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN 374). If applicable Protective nitrile gloves (EN 374). Protective gloves made of polyvinyl alcohol (EN 374). Protective Viton® / fluoroelastomer gloves (EN 374). Minimum layer thickness in mm: 0,5Permeation time (penetration time) in minutes: >= 480 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended. GB (RL M)-

Page 10 of 19 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 30.11.2020 / 0012 Replacing version dated / version: 10.11.2020 / 0011 Valid from: 30.11.2020 PDF print date: 02.12.2020 WD-40® Bike® All Conditions Lube WD-40® Specialist® Bike® All Conditions Lube

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

3.1 mormation on basic physical and chemical p	o open des
Physical state:	Aerosol. Active substance: liquid.
Colour:	Light yellow
Odour:	Perfumed
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	Not determined
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Not determined
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive. When using: development of explosive
	vapour/air mixture possible.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 ReactivityThe product has not been tested.10.2 Chemical stability

Stable with proper storage and handling. **10.3 Possibility of hazardous reactions**

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents. Avoid contact with strong alkalis.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-						
RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	>18,5	mg/l/4h	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Repeated
					Irritation/Corrosion)	exposure may
						cause skin
						dryness or
						cracking.
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact)
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative,
					Reverse Mutation	Analogous
					Test)	conclusion

- (B) (B) (M)
Page 12 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 30.11.2020 / 0012
Replacing version dated / version: 10.11.2020 / 0011
Valid from: 30.11.2020
PDF print date: 02.12.2020
WD-40 [®] Bike [®] All Conditions Lube
WD-40® Specialist® Bike® All Conditions Lube

Carcinogenicity:		OECD 453	Negative,
		(Combined Chronic	Analogous
		Toxicity/Carcinogenicit	conclusion
		y Studies)	001101010101
Reproductive toxicity:		OECD 414 (Prenatal	Negative,
		Developmental	Analogous
		Toxicity Study)	conclusion
Specific target organ toxicity -		<u> </u>	May cause
single exposure (STOT-SE):			drowsiness or
			dizziness.,
			STOT SE 3,
			H336
Aspiration hazard:			Yes
Symptoms:			unconsciousnes
			s, headaches,
			dizziness,
			discoloration of
			the skin,
			vomiting,
			diarrhoea
Specific target organ toxicity -		OECD 408 (Repeated	Not to be
repeated exposure (STOT-		Dose 90-Day Oral	expected
RE), oral:		Toxicity Study in	
		Rodents)	

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	2764	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Eye Irrit. 2
damage/irritation:					Eye	
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact)
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation	
					Test)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:					OECD 475	Negative
					(Mammalian Bone	
					Marrow Chromosome	
					Aberration Test)	
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	
					Mutation Test)	
Reproductive toxicity:		1000	mg/kg	Rat	OECD 414 (Prenatal	Negative,
					Developmental	Analogous
					Toxicity Study)	conclusion
Aspiration hazard:						No

Symptoms:					breathing difficulties, respiratory distress, diarrhoea, coughing, mucous membrane irritation, dizziness, watering eyes, nausea
Specific target organ toxicity - repeated exposure (STOT- RE), oral:	NOAEL	250	mg/kg	Rat	
Specific target organ toxicity - repeated exposure (STOT- RE), dermal:	NOAEL	>2000	mg/kg	Rat	
Specific target organ toxicity - repeated exposure (STOT- RE), inhalat.:	NOAEL	14	ppm	Rat	Vapours

Hydrocarbons, C6, isoalkan	Hydrocarbons, C6, isoalkanes, <5% n-hexane								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Acute toxicity, by oral route:	LD50	>16750	mg/kg	Rat	OECD 401 (Acute				
					Oral Toxicity)				
Acute toxicity, by dermal	LD50	>3350	mg/kg	Rabbit	OECD 402 (Acute				
route:					Dermal Toxicity)				
Acute toxicity, by inhalation:	LC50	259354	mg/m3	Rat	OECD 403 (Acute				
					Inhalation Toxicity)				
Skin corrosion/irritation:						Skin Irrit. 2			
Respiratory or skin				Mouse	OECD 429 (Skin	No (skin			
sensitisation:					Sensitisation - Local	contact)			
					Lymph Node Assay)				
Aspiration hazard:						Asp. Tox. 1			
Symptoms:						drowsiness,			
						unconsciousnes			
						S,			
						heart/circulatory			
						disorders,			
						headaches,			
						cramps,			
						drowsiness,			
						mucous			
						membrane			
						irritation,			
						dizziness,			
						nausea and			
						vomiting.			

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg		OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	>2000	mg/kg		OECD 402 (Acute	
route:					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit		Not irritant,
damage/irritation:						Analogous
						conclusion

Petroleum gases, liquefied								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by inhalation:	LC50	>5	mg/l					

- 68 R. M								
Page 14 of 19			()					
Safety data sheet accor				0 1907/2006	6, Annex II			
Revision date / version: Replacing version dated				711				
Valid from: 30.11.2020		JII. 10.11	.2020 / 00	511				
PDF print date: 02.12.20	020							
WD-40® Bike® All Cond								
WD-40® Specialist® Bi	ike® All	Conditio	ns Lube					
Skin corrosion/irritation:								Not irritant
Serious eye								Not irritant
damage/irritation:								
Respiratory or skin								No (skin
sensitisation: Aspiration hazard:								contact) No
								110
			0-0-1					
			SECTION	JN 12: E	cologic	al information		
				_				
Possibly more information			ntal effect	s, see Sect	ion 2.1 (cla	ssification).		
WD-40® Bike® All Cor WD-40® Specialist® E			tions Lub	<u>م</u>				
Toxicity / effect	Endp		Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:								n.d.a.
12.1. Toxicity to								n.d.a.
daphnia:								ndo
12.1. Toxicity to algae: 12.2. Persistence and								n.d.a. n.d.a.
degradability:								
12.3. Bioaccumulative								n.d.a.
potential:								
12.4. Mobility in soil: 12.5. Results of PBT								n.d.a. n.d.a.
and vPvB assessment								1.0.0.
12.6. Other adverse								n.d.a.
effects:				0.4	0(
Other information:				<0,1	%			of components with unknown
								hazards to the
								aquatic
								environment.
Hydrocarbons, C9-C11	1. n-alka	anes isc	alkanes.	cvclics. <2	% aromati	ics		
Toxicity / effect	Endp		Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEL	R	28d	0,13	mg/l	Oncorhynchus	QSAR	
12.1. Toxicity to	EC50		48h	>1000	mg/l	mykiss Daphnia magna	OECD 202	
daphnia:	ECSU		4011	>1000	ing/i	Daprinia magna	(Daphnia sp.	
							Acute	
							Immobilisation	
12.1. Toxicity to algae:	ErC50	<u>ר</u>	72h	>1000	mg/l	Pseudokirchnerie	Test) OECD 201	
12.1. TOXICITY TO algae.		5	1211	21000	ilig/i	lla subcapitata	(Alga, Growth	
							Inhibition Test)	
12.1. Toxicity to algae:	EbC5	0	72h	>1000	mg/l	Pseudokirchnerie		
						lla subcapitata	(Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEL	R	72h	100	mg/l	Raphidocelis	OECD 201	
		-				subcapitata	(Alga, Growth	
							Inhibition Test)	
12.1. Toxicity to fish:	LC50		96h	>1000	mg/l	Oncorhynchus	OECD 203	
						mykiss	(Fish, Acute Toxicity Test)	
12.2. Persistence and			28d	80	%		OECD 301 F	Readily
degradability:							(Ready	biodegradable
							Biodegradability -	
							Manometric Respirometry	
							Test)	
12.1. Toxicity to algae:	NOEL	R	72h	3	mg/l	Pseudokirchnerie	OECD 201	
						lla subcapitata	(Alga, Growth	
12.3. Bioaccumulative				5-6,7			Inhibition Test)	High
potential:				0 0,7				
	•			•	· ·	•	·	•

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
2-(2-butoxyethoxy)eth	anol						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to algae:	NOEC/NOEL	96h	>100	mg/l	Desmodesmus	OECD 201	
					subspicatus	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to	NOEC/NOEL	48h	>=100	mg/l	Daphnia magna	OECD 202	
danhaia						(Dephysic an	

12.1. Toxicity to daphnia:	NOEC/NOEL	48n	>=100	mg/I	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to bacteria:	EC10	30min	>1995	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
12.1. Toxicity to fish:	LC50	96h	1300	mg/l	Lepomis macrochirus	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.2. Persistence and degradability:		28d	76	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	
12.2. Persistence and degradability:		28d	100	%	activated sludge	OECD 302 B (Inherent Biodegradability - Zahn- Wellens/EMPA Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		1			OECD 117 (Partition Coefficient (n- octanol/water) - HPLC method)	Slight
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

Hydrocarbons, C6, isoalkanes, <5% n-hexane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	28d	4,09	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	7,14	mg/l	Daphnia magna	QSAR	

12.1. Toxicity to daphnia:	LC50	48h	3,87	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to algae:	ErC50	72h	55	mg/l	Pseudokirchnerie Ila subcapitata		Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	13,56	mg/l	Pseudokirchnerie Ila subcapitata	QSAR	
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable (Analogous conclusion), Analogous conclusion
12.3. Bioaccumulative potential:	Log Kow		4				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Benzene, mono-C10-1	3-alkyl derivat	ives, distil	lation resid	dues, sulfo	nated, sodium salts		
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Oncorhynchus	OECD 203	
					mykiss	(Fish, Acute	
						Toxicity Test)	
12.2. Persistence and		28d	8,6	%		OECD 301 F	Analogous
degradability:						(Ready	conclusion
						Biodegradability -	
						Manometric	
						Respirometry	
						Test)	
12.1. Toxicity to	EL50	48h	>100	mg/l	Daphnia magna	OECD 202	Analogous
daphnia:						(Daphnia sp.	conclusion
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EL50	72h	>100	mg/l	Desmodesmus	OECD 201	Analogous
					subspicatus	(Alga, Growth	conclusion
						Inhibition Test)	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	147,54	mg/l		QSAR	
12.3. Bioaccumulative							Not to be
potential:							expected
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substand

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations. 15 01 04 metallic packaging

- @B RI M			
Page 17 of 19			
Safety data sheet according to Re		Annex II	
Revision date / version: 30.11.20 Replacing version dated / version			
Valid from: 30.11.2020	. 10.11.2020 / 0011		
PDF print date: 02.12.2020			
WD-40® Bike® All Conditions Lu			
WD-40® Specialist® Bike® All C	onditions Lube		
15 01 10 packaging containing re		hazardous substances	
Do not perforate, cut up or weld u	ncleaned container.		
	SECTION 14: T	ransport information	
General statements			
14.1. UN number:		1950	
Transport by road/by rail	(ADR/RID)		
14.2. UN proper shipping name:			
UN 1950 AEROSOLS		. <i>t</i>	<u> </u>
14.3. Transport hazard class(es): 14.4. Packing group:		2.1	
Classification code:		- 5F	
LQ:		1 L	
14.5. Environmental hazards:		Not applicable	
Tunnel restriction code:	1->	D	
Transport by sea (IMDG-	code)		
14.2. UN proper shipping name: AEROSOLS			
14.3. Transport hazard class(es):		2.1	
14.4. Packing group:		-	•
EmS: Morino Dollutonti		F-D, S-U	
Marine Pollutant: 14.5. Environmental hazards:		n.a Not applicable	
Transport by air (IATA)			
14.2. UN proper shipping name:			
Aerosols, flammable			
14.3. Transport hazard class(es):		2.1	
14.4. Packing group: 14.5. Environmental hazards:		- Not applicable	
14.6. Special precautions	s for user		
Persons employed in transporting		ained.	
All persons involved in transportir		tions.	
Precautions must be taken to pre	0		_
14.7. Transport in bulk a Freighted as packaged goods rat		f MARPOL and the IBC Code	e
Minimum amount regulations hav			
Danger code and packing code o		-	
Comply with special provisions.			
	SECTION 15: Re	egulatory information	
15.1 Safaty boolth and a	nvironmontal regulativ	onclogiciation chooific for t	ha substance or mixture
15.1 Salety, fleatth and e	invironmentai regulatio	ons/legislation specific for t	ne substance of mixture
Observe restrictions:			
Comply with national regulations/	laws governing the protection	of young people at work (national imp	plementation of the Directive
94/33/EC)!	nnov XV/II		
Regulation (EC) No 1907/2006, A 2-(2-butoxyethoxy)ethanol			
Comply with trade association/oc	cupational health regulations.		
Directive 2012/18/EU ("Seveso II	I"), Annex I, Part 1 - The follow	wing categories apply to this product (others may also need to be
considered according to storage,			
Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for

 P3a
 11.1
 150 (netto)
 500 (netto)

 The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.
 150 (netto)
 500 (netto)

 P3a

the application of - Upper-tier requirements

Directive 2010/75/EU (VOC): **REGULATION (EC) No 648/2004** n.a.

~ 71,3 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

1

F00263

Revised sections:

Employee training in handling dangerous goods is required. These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Asp. Tox. — Aspiration hazard STOT SE — Specific target organ toxicity - single exposure - narcotic effects Aerosol — Aerosols Flam. Liq. — Flammable liquid Eye Irrit. — Eye irritation Skin Irrit. — Skin irritation Aquatic Chronic — Hazardous to the aquatic environment - chronic Skin Sens. — Skin sensitization

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approximately approx. Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BSEF The International Bromine Council body weight bw **Chemical Abstracts Service** CAS CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

39 (R) (M)
Page 19 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 30.11.2020 / 0012
Replacing version dated / version: 10.11.2020 / 0011
Valid from: 30.11.2020
PDF print date: 02.12.2020
WD-40® Bike® All Conditions Lube
WD-40® Specialist® Bike® All Conditions Lube
CMR carcinogenic, mutagenic, reproductive toxic
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EC European Community
ECHA European Chemicals Agency
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLIDInternational Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
OECD Organisation for Economic Co-operation and Development
org. organic
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning
the Registration, Evaluation, Authorisation and Restriction of Chemicals (REGOLATION (EC) No 1907/2000 concerning
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical
identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via
REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the
International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
wwt wet weight
The second state is the second s
The statements made here should describe the product with regard to the necessary safety precautions - they are
not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.
These statements were made by:
Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax:

+49 5233 94 17 90

 $^{\odot}$ by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.