stay connected

CUBE67+ BUSNODE

Profibus DP


Cube67+ PROFIBUS DP

Housing fully potted. For connection cables please see chapter "Connection Technology" Cube67+ modules can only be operated on Cube67+, Profibus + ProfiNet bus nodes.

Link to Product

Illustration





Product may differ from Image

Approvals





More Info



Connections

Fieldbus M12, B-coded



stay connected

Sensor-system/actuator supply	7/8", 5-pole, 2 × max. 8 A
Internal system connection	M12, 6 pole; max. 4 A
Fieldbus	
Operating modes	Sync- and freeze mode are supported
Transfer rate	to 12 Mbit/s
Addressing	Rotary switch 099
I/O capacity	with modular expandability by up to 32 Cube-modules
General data	
Protection	IP67
Mounting method	2-hole screw mounting
Temperature range	0+55 °C (storage temperature -20+75 °C)
Dimensions H × W × D	151×62×40.5 mm
Module Supply	
Operating voltage	24 V DC (EN 61131-2)
Current consumption	max. 120 mA
Diagnostic	
Communication status	per LED and BUS
Diagnostic via LED	per module and channel
Diagnostic via BUS	per module and channel
Monitoring - under voltage	yes
Monitoring - no voltage	yes
Short circuit and overload	yes
Commercial data	
country of origin	DE
customs tariff number	85176200
minimum order quantity	1