



# **MASTER MHN-LA**

## **MASTER MHN-LA 1000W/842 230V XWH**

Compact quartz metal halide lamps with double-pinch

#### **Warnings and Safety**

- $\cdot$  Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**

General Information	
Cap-Base	X528 [ X528]
Operating Position	P5 [ Parallel +/-5D or Horizontal(HOR)]
Life to 5% Failures (Nom)	6000 h
Life To 10% Failures (Nom)	8000 h
Life to 20% Failures (Nom)	10000 h
Life to 50% Failures (Nom)	15000 h
Light Technical	
Color Code	842 [ CCT of 4200K]
Luminous Flux (Rated) (Min)	85800 lm
Luminous Flux (Rated) (Nom)	95800 lm
Color Designation	Cool White (CW)
Lumen Maintenance 1000 h (Nom)	90 %
Lumen Maintenance 2000 h (Nom)	80 %
Chromaticity Coordinate X (Nom)	366
Chromaticity Coordinate Y (Nom)	370
Correlated Color Temperature (Nom)	4200 K
Luminous Efficacy (rated) (Nom)	92.00 lm/W
· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·

Color Rendering Index (Nom)	70
Operating and Electrical	
Lamp supply voltage	230 V [ 230]
Power (Nom)	1040.0 W
Lamp Current Run-Up (Max)	15 A
Lamp Current (EM) (Nom)	9.3 A
Ignition Supply Voltage (Min)	198 V
Voltage (Max)	140 V
Voltage (Min)	110 V
Voltage (Nom)	125 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear
Cap-Base Information	Cable


Datasheet, 2020, March 19 data subject to change

## **MASTER MHN-LA**

Approval and Application	
Energy Efficiency Label (EEL)	A+
Mercury (Hg) Content (Nom)	112 mg
Energy Consumption kWh/1000 h	1144 kWh
UV	
Specific Eff. Radiant Power	265 mW/klm
Luminaire Design Requirements	
Bulb Temperature (Max)	920 ℃
Pinch Temperature (Max)	350 ℃

Product Data	
Full product code	871150020078500
Order product name	MASTER MHN-LA 1000W/842 230V XWH
EAN/UPC - Product	8718291548232
Order code	928073005130
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	928073005130
Net Weight (Piece)	141.000 g
ILCOS Code	MN-1000-E-K-/H


## Dimensional drawing



Product	D (max)	0	X	Α
MASTER MHN-I A 1000W/842 230V XWH	40 mm	40.5 mm	35 mm	286 mm

MHN-LA 1000W/842 230V XWH


#### Photometric data




LDPO\_MHN-LA\_0001-Spectral power distribution Colour

## **MASTER MHN-LA**

#### Lifetime





LDLE\_MHN-LA\_0001-Life expectancy diagram

LDLM\_MHN-LA\_0001-Lumen maintenance diagram



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.