


Polyurethane PU Self-Adhesive Protective Feet - Square



DESCRIPTION

A range of square self-adhesive protective feet made from clear or black polyurethane (PU).

DISTINCTIVE FEATURES

- Wide range of sizes
- Quick and simple to fit
- Protects against scratching
- Helps prevent slipping and sliding
- Absorb shock and vibration
- Protects surfaces and equipment
- Non-marking
- Create gap for heat dissipation
- Supplied in sheet quantities

APPLICATIONS

Ideal for use with a wide range of products and applications.

PU

SQUARE

UL94-HB



GENERAL SPECIFICATION

Type	Square
Features	Shock & vibration resistant
	Non-slip & non-marking



MATERIALS

Material	Polyurethane
Colour	Clear or black

Polyurethane Physical Properties		
Properties	Test method	All colours
Hardness (Shore A)	ASTN D-2240	66-70
Tensile strength (MPA)	BS903	4.5MN/m ²
Elongation (%)	BS903	193
Tear strength (KN/m)	BS903	14.4
Abrasion resistance (MG loss)	BS EN 5470-1:1999	150
Load tolerance 21°C to 60°C	-	Min. 3 Mpa
Flame retardancy	UL94HB (in-house test)	Pass
Kinetic coefficient of friction	ASTM D - 1894 - 78	-
	A Stainless steel	2.52
	B Glass	2.7
	D High impact polystyrene	2.37
Shelf-life - 12 months when stored in original packaging at room temperature		

Exposure to the Environment

These feet are intended for interior applications where physical properties will remain unchanged. When used externally for extended periods, some discolouration as well as loss of adhesion may occur.

Pressure Sensitive Adhesive Data


A solvent based acrylic adhesive with high instant tack. Strong stable pressure sensitive adhesive system which displays good adhesion to more demanding surfaces that would need higher levels of tack as well as good peel and shear properties. This adhesive system also displays good ageing properties when used for long term applications

Peel & Sheet Data			
Surface material	Test method	4001 Pressure Sensitive Adhesive Data	
		20 min. - 23°C 50% RH	24 hour - 23°C 50% RH
Stainless steel	Peel FINAT 1	13.4	15.7
Aluminium	Unit N/25mm	12.1	14.8
Glass		12.5	17.7
HDPE		4.1	4.4
Polystyrene		9.9	13.1
ABS		10.4	15.1
Stainless steel	Shear FINAT 8	—	>300 hour
Stainless steel	Loop tack N/25mm	13.8	

Temperature Range			
Adhesive No.	Adhesive type	Application temperature	Service temperature
4001	Solvent	20°C to +40°C	-40°C to +120°C

Adhesive Considerations

Please refer to the chart which illustrates the relative adhesion properties of the adhesive system. In general terms it is helpful to allow time (dwell) to increase the surface contact and therefore the overall adhesion. As application conditions will vary, we recommend customers carry out their own tests to ensure suitability.



It is important to remember, that as with any self adhesive product, the surface to which they are being applied must be clean, dry and free from dust and dirt. Therefore, to gain maximum adhesion, clean the surface with low strength solvent and allow to dry thoroughly before use.



CERTIFICATION AND STANDARDS

ASTN D-2240	BS EN 5470-1:1999
BS903	ASTM D - 1894 - 78



ENVIRONMENTAL/OPERATING SPECIFICATION

Flame Resistance	UL94-HB
Load Tolerance 21°C to 60°C	3Mpa min.



DIMENSIONS/DRAWINGS

Dimensions	mm – see Part Number Table
------------	----------------------------



PART NUMBER TABLE

Part Number Units	Length x width mm	Height mm	Colour	Sheet quantity	EAN	UNSPSC	Country of Origin
31-0006	10 x 10	2.5	Clear	110	5053556003426	30161809	United Kingdom
31-0008	12.6 x 12.6	5.7	Clear	100	5053556003440	30161809	United Kingdom
31-0007	12.7 x 12.7	3.1	Clear	100	5053556003433	30161809	United Kingdom
31-0009	20.5 x 20.5	7.5	Clear	78	5053556003457	30161809	United Kingdom
31-0022	10 x 10	2.5	Black	110	5053556003587	30161809	United Kingdom
31-0023	12.7 x 12.7	3.1	Black	100	5053556003594	30161809	United Kingdom
31-0024	20.5 x 20.5	7.5	Black	78	5053556003600	30161809	United Kingdom
31-0030	20.5 x 20.5	13.2	Black	72	5053556003662	30161809	United Kingdom



Tried & trusted technology

Important Notice: This data sheet and its contents (the "Information") belong to Rapid Electronics Limited or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Rapid Electronics Limited assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Rapid Electronics Limited were aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict Rapid Electronics Limited's liability for death or personal injury resulting from its negligence.