

Printing date 28.02.2020

Version number 303

Revision: 28.02.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier 600069
- · Trade name: Silicone grease spray E-COLL
- · Article number: 4317784179607
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU21 Consumer uses: Private households / general public / consumersSU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Application of the substance / the mixture Lubricant

\cdot 1.3 Details of the supplier of the safety data sheet

 Manufacturer/Supplier: E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification


- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.





Printing date 28.02.2020

Version number 303

Revision: 28.02.2020

Trade name: Silicone grease spray E-COLL

(Contd. of page 1)

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C6, isoalkanes, <5% n-hexane

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P261 Avoid breathing mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.



Printing date 28.02.2020

Version number 303

Revision: 28.02.2020

Trade name: Silicone grease spray E-COLL

	(Cor	ntd. of page 2)
· Dangerous components:		
EC number: 931-254-9 Reg.nr.: 01-2119484651-34-XXXX	Hydrocarbons, C6, isoalkanes, <5% n-hexane Flam. Liq. 2, H225; S Asp. Tox. 1, H304; Aquatic Chronic 2, H411; S Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane, pure 🚸 Flam. Gas 1, H220; Press. Gas (Comp.), H280	25-50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220; 🔶 Acute Tox. 1, H330; Press. Gas (Comp.), H280	2.5-10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-10%
· Regulation (EC) No 648/2004 on detergents / Labelling for contents		
aliphatic hydrocarbons		≥30%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Do not induce vomiting; call for medical help immediately. Drink plenty of water and provide fresh air. Call for a doctor immediately.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

(Contd. on page 4)

FU



Printing date 28.02.2020

Version number 303

Revision: 28.02.2020

Trade name: Silicone grease spray E-COLL

(Contd. of page 3)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.
- Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow product to reach sewage system or any water course. Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation. Dispose contaminated material as waste according to item 13.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Use only in well ventilated areas.

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges. Do not spray onto a naked flame or any incandescent material.



Printing date 28.02.2020

Version number 303

Revision: 28.02.2020

Trade name: Silicone grease spray E-COLL

(Contd. of page 4) Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles:
 Store in a cool location.
 Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the skin.
- · Respiratory protection: Not necessary if room is well-ventilated.
- · Protection of hands:



Protective gloves

Recommendation: protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.



Printing date 28.02.2020

Version number 303

Revision: 28.02.2020

(Contd. of page 5)

Trade name: Silicone grease spray E-COLL

Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

\cdot 9.1 Information on basic physical and chemical properties

· General Information

 Appearance: Form: Colour: Odour: Odour threshold: 	Aerosol Colourless Characteristic Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/freezing point: Initial boiling point and boiling range 	Undetermined. Not applicable, as aerosol.
· Flash point:	Not applicable, as aerosol.
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	200 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Not determined.
 Explosion limits: Lower: Upper: Oxidising properties 	1.5 Vol % 8.5 Vol % Not determined.
 Vapour pressure at 20 °C: 	2800 hPa



Printing date 28.02.2020

Version number 303

Revision: 28.02.2020

Trade name: Silicone grease spray E-COLL

		(Contd. of page 6)
· Density at 20 °C:	0.67 g/cm³	
· Relative density	Not determined.	
 Vapour density Evaporation rate 	Not determined. Not applicable.	
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
 Viscosity: Dynamic: Kinematic: Organic solvents: VOC (EC) % VOCV (CH) 	Not determined. Not determined. 74.9 % 501,8 g/l 74,90 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

CAS: 106-97-8 butane, pure

Inhalative LC50/4h 658 ppm (rat)

(Contd. on page 8)

EU —



Printing date 28.02.2020

Version number 303

Revision: 28.02.2020

(Contd. of page 7)

Trade name: Silicone grease spray E-COLL

CAS: 74-98-6 propane

Inhalative LC50/4h >20 mg/m3 (rat)

- · Primary irritant effect:
- **Skin corrosion/irritation** Causes skin irritation.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Toxic for aquatic organisms Also poisonous for fish and plankton in water bodies.



Printing date 28.02.2020

Version number 303

Revision: 28.02.2020

Trade name: Silicone grease spray E-COLL

(Contd. of page 8)

\cdot 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

• **13.1 Waste treatment methods:** Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue

16 05 04*gases in pressure containers (including halons) containing hazardous substances15 01 10*packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information	n
--	---

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
 14.2 UN proper shipping name ADR 	UN1950 AEROSOLS, ENVIRONMENTALLY
·IMDG	HAZARDOUS AEROSOLS (Naphtha (petroleum), hydrotreated light (Benzene < 0.1%)), MARINE POLLUTANT
	AEROSOLS
· 14.3 Transport hazard class(es)	
· ADR	
· Class · Label	2 5F Gases. 2.1
·IMDG	
· Class	2 Gases. (Contd. on page 10)
	EU



Printing date 28.02.2020	Version number 303	Revision: 28.02.2020	
Trade name: Silicone grease spray E	-COLL		
· Label	2.1	(Contd. of page 9)	
·IATA			
· Class · Label	2 Gases. 2.1		
 · 14.4 Packing group · ADR 	Void		
· 14.5 Environmental hazards:		Product contains environmentally hazardous substances: Naphtha (petroleum), hydrotreated light (Benzene < 0.1%)	
· Marine pollutant:	Yes Symbol (fish and tree)		
· Special marking (ADR):	Symbol (fish and tree)		
 • 14.6 Special precautions for user • EMS Number: 	Warning: Gases. F-D,S-U		
 14.7 Transport in bulk according t Marpol and the IBC Code 	o Annex II of Not applicable.		
· Transport/Additional information:			
 ADR Limited quantities (LQ) Transport category Tunnel restriction code UN "Model Regulation": 	1L 2 D UN1950, AEROSOLS, E HAZARDOUS, 2.1	ENVIRONMENTALLY	

SECTION 15: Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Labelling according to Regulation (EC) No 1272/2008
 The product is classified and labelled according to the CLP regulation.
 Hazard pictograms



· Signal word Danger

(Contd. on page 11)



Printing date 28.02.2020

Version number 303

Revision: 28.02.2020

Trade name: Silicone grease spray E-COLL

(Contd. of page 10)

· Hazard-determining components of labelling:

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Hazard statements

- H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P261 Avoid breathing mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I Methanol
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H330 Fatal if inhaled.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- · Department issuing SDS: Product safety department
- **Contact:** Head of Product Safety Department

Printing date 28.02.2020

Version number 303

Revision: 28.02.2020

Trade name: Silicone grease spray E-COLL

(Contd. of page 11)

· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1 Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Acute Tox. 1: Acute toxicity - inhalation – Category 1 Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

·* Data compared to the previous version altered.

EU ----

